



Equipped with LEDs in a neutral white light colour [4,000 K], the TRIPROOF LED IP65 damp-proof light consists of a light grey polycarbonate housing and a satin-finished polycarbonate cover in one piece. It is suitable for simple ceiling, wall or suspended mounting and is available in three different lengths. Several lights can be connected in series; ideal for industrial and private use, e.g. for lighting under canopies, in cellar rooms, workshops, garages, industrial halls etc. The light has a simple electrical connection with push-in connector.

Special features

- High impact resistance
- Feed-through wiring possible

Housing Material	Plastic	Power Consumption	17 kWh/1000h
Housing Color	White	Energy Efficiency Class	G
Housing Surface	Matt		
Protection Class	Protection class II/protective insulation		
Rated Input	17 W		
Rated Input Voltage Frequency	180-240 V/AC 50 / 60 Hz		
Power Supply Unit incl.	Yes		
Connection Type	Clamp		
Dimmable	No		
Motion Detector	No		
Light Source	LED, Light source not changeable		
Color Temperature	4000 K		
Colour Consistency	6 SDCM		
Colour Rendering Index (Ra)	80		
Rated Luminous Flux	1430 lm		
Rated Angle of Reflection	120 Degree		
Distribution Characteristic 120°	NDLS		
Light Exit Surfaces	1		
Light characteristics	Direct		
Light direction	Below		
Length	696 mm		
Width	61 mm		
Height	56 mm		
Working Temperature	-20 to 40 °C		
Storage Temperature	-10 to 60 °C		
IP Protection Class	IP 65		
Life Time L70 / B50	35000 h		
Switching Cycles	15000		

