


LED surface-mounted spot CIRCLE, with all-round light gap  
**Artikel-Nr. 12061073**



LED surface-mounted spot CIRCLE, with all-round light gap, white, round. Surface mounting, Ceiling-mounted Mounting method: Surface mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Glass, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) I, Voltage: 230V AC 50Hz, Power: 9.8W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 675lm, Colour temperature: 3.000 K, Light colour : White, Beam angle: 34°, Adjustability: Rotatable and adjustable head, With control gear: Yes, Control: on/off.

|                                    |                                                           |                       |                               |
|------------------------------------|-----------------------------------------------------------|-----------------------|-------------------------------|
| Artikel-Nr.                        | 12061073                                                  |                       |                               |
| Stand:                             | 07.12.2021 12:07                                          |                       |                               |
| Colour temperature                 | 3000 K                                                    | Outer diameter        | 100 mm                        |
| Colour                             | White                                                     | Voltage               | 230V AC 50Hz                  |
| Beam angle                         | 34 °                                                      | Luminous flux         | 675 lm                        |
| Amount of light sources / fittings | 1 Qty                                                     | Degree of protection  | IP20                          |
| Material                           | Aluminium / Glass                                         | Protection class      | I                             |
| Power                              | 9,8 W                                                     | Adjustability         | Rotatable and adjustable head |
| Lamp                               | LED                                                       | Aufbauhöhe            | 105 mm                        |
| scope of delivery                  | Incl. converter for connection to the 230-V mains voltage | Rotation angle        | 355 °                         |
| Colour rendering                   | CRI > 80                                                  | Swivel angle          | 90 °                          |
| Control                            | on/off                                                    | Head adjustable angle | 90 °                          |
|                                    |                                                           | Circuit type          | Parallel conduction           |