



The APOLLON narrow, puristic pendant lamp fits into almost any environment seamlessly and in addition to the elegant visual design also delivers a rich warm white light. The APOLLON is available in two different sizes with a matte surface in black and white.

Special features

- Especially narrow design
- High colour rendering
- Suspended mounting up to max. 3,000 mm
- Dimmable

| | | | |
|---|---|--------------------------------|--------------|
| Housing Material | Aluminium | Working Temperature | -20 to 40 °C |
| Housing Color | White | Storage Temperature | -30 to 60 °C |
| Housing Surface | Matt | IP Protection Class | IP 20 |
| Protection Class | Protection class II/protective insulation | Life Time L70 / B50 | 50000 h |
| Rated Input | 28 W | Switching Cycles | 25000 |
| Rated Input Voltage Frequency | 200-250 V/AC 50 / 60 Hz | Power Consumption | 28 kWh/1000h |
| Power Supply Unit incl. | Yes | Energy Efficiency Class | G |
| Connection Type | Clamp | | |
| Dimmable | Yes | | |
| Control technology | Leading-edge dimmer, Trailing-edge dimmer | | |
| Motion Detector | No | | |
| Light Source | LED, Light source not changeable | | |
| Color Temperature | 2700 K | | |
| Colour Consistency | 6 SDCM | | |
| Colour Rendering Index (Ra) | 90 | | |
| Rated Luminous Flux | 1755 lm | | |
| Rated Angle of Reflection | 110 Degree | | |
| Light Distribution | Symmetric | | |
| Distribution Characteristic 120° | DLS | | |
| Light Exit Surfaces | 2 | | |
| Light characteristics | Direct, Indirect | | |
| Light direction | Top, Below | | |
| Length | 1004 mm | | |
| Width | 80 mm | | |
| Height | 8 mm | | |
| Base length | 650 mm | | |
| Base width | 35 mm | | |
| Base height | 48 mm | | |
| Pendulum Length max. | 3000 mm | | |