

## Han-Port Combi insert D/HIFF breakout



Image is for illustration purposes only. Please refer to product description.

Part number	39 50 001 0450
Specification	Han-Port Combi insert D/HIFF breakout
HARTING eCatalogue	<a href="https://b2b.harting.com/39500010450">https://b2b.harting.com/39500010450</a>

### Identification

Category	Sockets
Series of hoods/housings	Han-Port®
Element	Socket
Specification	2 cut-outs for HIFF data module

### Version

Termination method	Spring clamp termination
Field of application	Germany (VDE)

### Termination data

Supply voltage	250 V AC
Nominal current	16 A
Nominal frequency	50 Hz

### Technical characteristics

Conductor cross-section	2.5 mm <sup>2</sup>
Mounting depth	43 mm

### Material properties

Material (hood/housing)	Thermoplastic
RoHS	compliant
ELV status	compliant
China RoHS	e



**Pushing Performance**  
Since 1945

## Material properties

REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained

## Commercial data

Packaging size	1
Net weight	80 g
Country of origin	Germany
European customs tariff number	85366990
GTIN	5713140190467
eCl@ss	27144042 Plug socket