



Recessed ceiling lights can be subtly integrated into private and commercial spaces, yet when it comes to replacing, the existing ceiling cut-out can present a problem. The ZAURAK series comes with an adjustable mounting clip, which can be used with larger and smaller ceiling cut-outs. In addition, the ZAURAK has a low installation depth for universal use. Two exchangeable cover rings in silver and black are included in the scope of delivery.

**Special features**

- Light colour adjustable in 3 stages
- Power adjustable in 2 stages
- Adjustable cut-out dimension
- Including 2 colour rings (black/silver)

<b>Housing Material</b>	Plastic
<b>Housing Color</b>	White
<b>Material of Lens</b>	Plastic
<b>Protection Class</b>	Protection class II/protective insulation
<b>Power Selectable</b>	18 W, 25 W
<b>Rated Input Voltage Frequency</b>	220-240 V/AC 50 / 60 Hz
<b>Power Supply Unit incl.</b>	Yes
<b>Connection Type</b>	Clamp
<b>Dimmable</b>	No
<b>Motion Detector</b>	No

<b>Life Time L70 / B50</b>	30000 h
<b>Switching Cycles</b>	15000
<b>Power Consumption</b>	25 kWh/1000h
<b>Energy Efficiency Class</b>	G

<b>Light Source</b>	LED, Light source not changeable
<b>Color Temperature</b>	3000/4000/5700 K
<b>Colour Consistency</b>	6 SDCM
<b>Colour Rendering Index (Ra)</b>	80
<b>Rated Luminous Flux</b>	2420 lm
<b>Luminous Efficiency</b>	96.8 lm/W
<b>Rated Angle of Reflection</b>	110 Degree
<b>Distribution Characteristic 120°</b>	DLS

<b>Light Exit Surfaces</b>	1
<b>Light characteristics</b>	Direct
<b>Light direction</b>	Below

<b>Height</b>	25 mm
<b>Diameter</b>	300 mm
<b>Cut Out Diameter</b>	150-270 mm
<b>Product weight</b>	1100 g

<b>Working Temperature</b>	-20 to 0 °C
<b>Storage Temperature</b>	-20 to 40 °C
<b>IP Protection Class</b>	IP 44
<b>IK Protection Class</b>	IK03

