

## Han S 200 CA-c-b/r 25mm<sup>2</sup> 0,5m



Part number	33 50 686 9248 005
Specification	Han S 200 CA-c-b/r 25mm <sup>2</sup> 0,5m
HARTING eCatalogue	<a href="https://b2b.harting.com/33506869248005">https://b2b.harting.com/33506869248005</a>

Image is for illustration purposes only. Please refer to product description.

### Identification

Category	System cabling
Series	Han® S
Element	Cable assemblies
Specification	Pre-assembled on both sides
Connector 1	Female Angled Black
Connector 2	Female Angled Red
Type of cable	Copper cable (round)
Description of the cable	Oil resistant High fuel resistance Resistance to ozone Weathering resistant

### Version

Cable length	0.5 m
Number of cores	1
Core structure	25 mm <sup>2</sup>
Details	Not be coupled or decoupled under electrical load. Assembly and installation must be carried out by a qualified electrician.

### Technical characteristics

Rated current	130 A
Rated voltage	1,500 V
Rated impulse voltage	8 kV

## Technical characteristics

Pollution degree	2
Insulation resistance	>10 <sup>8</sup> Ω
Limiting temperature	-40 ... +120 °C unmoved -40 ... +90 °C moved
Number of relockings	≥500
Degree of protection acc. to IEC 60529	IP40 mated condition IP20 unmated condition (1500 V DC; 1000 V AC)
Cable diameter	10.2 mm

## Material properties

Material (cable)	Polyolefin copolymer
Colour (cable)	Black

## Specifications and approvals

Specifications	EN 50264-3-1 EN 60811-403 Resistance to ozone EN 60811-504 High low temperature resistance EN 60811-404 Oil resistance EN 60811-404 High fuel resistance EN 60811-404 Acid resistance EN 60811-404 Alkali resistance DIN 51900 Low fire load ISO 4589-2 Limiting Oxygen Index (LOI) EN 50618 UV resistant UN/ECE-R 118 fire protection for rolling stock ISO 6722-1
----------------	--

## Commercial data

Packaging size	1
Country of origin	Germany
European customs tariff number	85444290
GTIN	5713140262263
eCl@ss	27060307 Bus cable