

Panel mounting socket outlet, angled - lockable, flange 74x62



| Product description | |
|---------------------------|--|
| BALS-Prd.-Nr | 12990 |
| EAN | 4024941129909 |
| Product category | Panel mounting socket outlet Quick-Connect, angled |
| Current | 16A |
| Number of poles | 3p |
| Poles | 2P+PE |
| Position of earth contact | 6 h |
| Voltage | 200 up to 250V |

| Product description | |
|--------------------------------|--|
| Frequency | 50 and 60Hz |
| Protection degree | IP44 |
| Colour code | blue RAL 5015 |
| Colour of appliance | Hinged lid blue RAL 5015, Enclosure grey RAL 7035 |
| Connection design | screwless spring terminals as cage clamp with Kontex-contact |
| Maximum conductor size | 4,0 qmm |
| Cable entry | other |
| Height | 77mm |
| Width | 63mm |
| Depth | 94mm |
| Flange size vertical | 74mm |
| Flange size horizontal | 62mm |
| Drill hole distance vertical | 60mm |
| Drill hole distance horizontal | 52mm |
| Material of enclosure | Polyamide |
| Contact | The contact carrier is made of polyamide, The contacts are brass |

| Additional technical properties | |
|---------------------------------|---|
| | The inclination is 20° |
| | Lockable with padlock bow diameter 5 mm |

| Logistics data | |
|----------------|------------------|
| Weight/pcs | 0.097 kg / Piece |
| Packaging | Bag |
| Content amount | 1 ST |
| EAN | 4024941129909 |
| Length | 94 mm |
| Width | 63 mm |
| Height | 77 mm |
| Weight | 0.098 kg |
| Volume | 455.994 ccm |
| Packaging | Carton |
| Content amount | 10 ST |
| EAN | 4024941821001 |
| Length | 207 mm |
| Width | 162 mm |
| Height | 142 mm |
| Weight | 1.07 kg |
| Volume | 3,750 ccm |

