

Panel mounting socket outlet, angled - flange 100x92, fixing centers 85x77



| Product description | |
|---------------------------|----------------------------------------------------|
| BALS-Prd.-Nr | 12785 |
| EAN | 4024941127851 |
| Product category | Panel mounting socket outlet Quick-Connect, angled |
| Current | 16A |
| Number of poles | 5p |
| Poles | 3p+N+PE |
| Position of earth contact | 7 h |
| Voltage | 277/480 up to 288/500V |

| Product description | |
|--------------------------------|------------------------------------------------------------------|
| Frequency | 50 and 60Hz |
| Protection degree | IP44 |
| Colour code | black RAL 9005 |
| Colour of appliance | Hinged lid black RAL 9005, Enclosure grey RAL 7035 |
| Connection design | screwless spring terminals as cage clamp with Kontex-contact |
| Maximum conductor size | 4,0 qmm |
| Cable entry | other |
| Height | 100mm |
| Width | 92mm |
| Depth | 96mm |
| Flange size vertical | 100mm |
| Flange size horizontal | 92mm |
| Drill hole distance vertical | 85mm |
| Drill hole distance horizontal | 77mm |
| Material of enclosure | Polyamide |
| Contact | The contact carrier is made of polyamide, The contacts are brass |

| Additional technical properties | |
|---------------------------------|------------------------|
| | The inclination is 20° |

| Logistics data | |
|----------------|------------------|
| Weight/pcs | 0.157 kg / Piece |
| Packaging | Bag |
| Content amount | 1 ST |
| EAN | 4024941127851 |
| Length | 96 mm |
| Width | 92 mm |
| Height | 100 mm |
| Weight | 0.158 kg |
| Volume | 883.2 ccm |
| Packaging | Carton |
| Content amount | 10 ST |
| EAN | 4024941829663 |
| Length | 245 mm |
| Width | 177 mm |
| Height | 185 mm |
| Weight | 1.703 kg |
| Volume | 7,140 ccm |



| Ampere | 16 | 16 | 16 | 32 | 32 | 32 |
|----------------------------|------|-------|-------|-------|-------|-------|
| Polzahl | 3 | 4 | 5 | 3 | 4 | 5 |
| a | 74,0 | 100,0 | 100,0 | 100,0 | 100,0 | 100,0 |
| b | 62,0 | 92,0 | 92,0 | 92,0 | 92,0 | 92,0 |
| c | 60,0 | 85,0 | 85,0 | 85,0 | 85,0 | 85,0 |
| d | 52,0 | 77,0 | 77,0 | 77,0 | 77,0 | 77,0 |
| e ø | 5,5 | 5,5 | 5,5 | 5,5 | 5,5 | 5,5 |
| f | 8,0 | 8,0 | 8,0 | 8,0 | 8,0 | 8,0 |
| h | 46,0 | 46,0 | 46,0 | 55,0 | 55,0 | 55,0 |
| i | 48,0 | 50,0 | 55,0 | 68,0 | 68,0 | 60,0 |
| k | 57,0 | 65,0 | 70,0 | 75,0 | 75,0 | 78,0 |
| l | 52,0 | 65,0 | 70,0 | 75,0 | 75,0 | 78,0 |
| α | 20° | 20° | 20° | 20° | 20° | 20° |
| Leiter mm ² min | 1,5 | 1,5 | 1,5 | 2,5 | 2,5 | 2,5 |
| Leiter mm ² max | 4 | 4 | 4 | 10 | 10 | 10 |