

**Special features**

- High colour reproduction value
- Swivel-mounted
- Chrome ring

Housing Material	Aluminium
Housing Color	White
Housing Surface	Shiny
Material of Lens	Glass
Surface Structure of Lens	Transparent
Protection Class	Protection class III/safety extra-low voltage
Operating Mode	Constant current
Rated Input	7 W
Rated Input Voltage	17-18 V/DC
Rated Current	350 mA
Power Supply Unit incl.	No
Connection Type	Adapter
Dimmable	Yes
Control technology	Dimmable via optional power supply unit
Motion Detector	No

Light Source	LED, Light source not changeable
Color Temperature	2700 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	700 lm
Luminous Efficiency	100 lm/W
Rated Angle of Reflection	30 Degree
Light Distribution	Symmetric
Distribution Characteristic 120°	DLS

Swivel Angle	25 Degree
Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below

Height	49 mm
Diameter	100 mm

Installation Depth	39 mm
Cut Out Diameter	73 mm
Product weight	180 g
Working Temperature	-5 to 40 °C
Storage Temperature	-25 to 40 °C
IP Protection Class	IP 20
Life Time L70 / B50	30000 h
Switching Cycles	50000
Power Consumption	7 kWh/1000h
Energy Efficiency Class	G