


VPC and LPC Fiber Patch Cords

APPLICATION

Fiber Optic Patch Cords are designed to interconnect, or cross-connect fiber networks within structured cabling systems for data centers, Broadband CATV, Passive Optical Networks (PON), WDM or DWDM multiplexing, FTTH, and voice services in ATM and SONET metropolitan and access networks. Common connector patch cord configurations in 1, 2, 3, 5, and 10-meter lengths are stocked for quick service, while hybrid connector combinations, custom lengths, low loss, and custom color patch cords are made to order. Contact customer service for details.



SPECIFICATION

Patch cords shall be compliant with ANSI/TIA-568.3-E. Standard insertion loss shall be a maximum of 0.25 dB for multimode and single-mode. Low loss shall be a maximum of 0.15 dB for multimode and single-mode connectors. Multimode return loss shall be greater than 26 dB and greater than 50 dB for single UPC mode connectors. Single-mode angled physical contact connectors (APC) shall have a minimum of 60 dB return loss. Patch cords shall have a pull force of at least 50 N per IEC 61300-2-4. Connector durability shall be greater than 500 matings for both multimode and single-mode. Patch cord shall be LSHF (Low Smoke Halogen Free) rated. Patch cords shall be individually packaged with part numbers, descriptions, optical performance, code 39 barcode part number printed on each package, and QR code to access supporting documentation. Patch cords shall include wrap labels including length, end designation, and serial number, providing traceability to factory collected test data.

DESIGN CONSIDERATIONS

- LSHF (Low Smoke Halogen Free), LSZH (Low Smoke Zero Halogen), HFFR-LS (Halogen Free Flame Retardant Low Smoke) rated
- All connectors have precision pre-radiused or pre-angled zirconia ferrules supporting consistent End Face Geometry (EFG)
- Single-mode available in UPC and APC polish
- FC and ST connectors have metal bodies
- Duplex clips included with LC and SC duplex configurations
- Bend-insensitive glass (OS2, OM3, and OM4 and OM5)
- Standard polarity is A-B

FEATURES

- Available in simplex, duplex, and pigtail configurations
- LC, LC Unibody with SPECTRO-LINK™ Technology, LC/APC, SC, SC/APC, ST, FC, and FC/APC connector options
- Stock and make-to-order
- TIA compliant color-coded connectors and boots
- Cable jacket and boots color-coded for easy ID of fiber
- Fiber options: OS2, OM1, OM3, OM4, and OM5
- 100% tested for insertion loss and single-mode for return loss
- LC Unibody connectors have patented reversible polarity features, allowing polarity changes in the field without tools
- The LC Unibody design with push/pull grips and 2.0 mm round cable is ideal for high-density applications
- Patch cords include a Limited Lifetime Warranty when used with other Leviton cabling and installed by a Leviton certified contractor
- Other jacket colors available as custom with MOQ and lead time applicable
- Cable contains Aramid strength members
- Custom configurations via [Leviton.com/mta](https://leviton.com/mta)

STANDARDS & REGULATIONS

- ANSI/TIA-568.3-E
- ISO/IEC 11801-1
- Fiber Optic Connector Intermatability Standards (FOCIS)
- TIA-604-10B (LC)
- TIA-604-3B (SC)
- TIA-604-2B (ST)
- TIA-604-4B (FC)

End face geometry:

- IEC 61755-3-1 (UPC/PC)
- IEC 61755-3-2 (APC)

Fiber compliance:

- OS2: IEC 60793-2-50, ITU-T G.657.A1
- OM1: IEC 60793-2-10
- OM3: IEC 60793-2-10, ITU-T G.651.1
- OM4: IEC 60793-2-10, ITU-T G.651.1
- OM5: IEC 60793-2-10, TIA 492AAAF, ITU-T G.651.1

Flame rating:

- LSHF / LSZH / HFFR
- IEC 60332-3-24, IEC 60332-1-2
- RoHS

COUNTRY OF ORIGIN

China
USA for LC Unibody Connector

PRODUCT SPECIFICATIONS

VPC and LPC Fiber Patch Cords

MECHANICAL SPECIFICATIONS

Connector Durability: > 500 Matings
 Connector Cable Retention: 50 N (11.24 lbf)

WARRANTY INFORMATION

For Leviton product warranties, go to Leviton.com/ns/warranty

FIBER PERFORMANCE


Cable Type	Fiber Count	Nominal Diameter (mm)	Weight (kg/km)	Tension (N)		Bend radius (mm)		Temperature Range (C°)	
				Installation	Long Term	Installation	Long Term	Operational	Storage
1.2 mm Duplex Zipcord	2	1.2 x 2.5	4 kg/km	50	30	24 mm	12 mm	-10 °C to +60 °C	-25 °C to +70 °C
1.6 mm Duplex Zipcord	2	1.6 x 3.2	6 kg/km	50	30	50 mm	30 mm		
2.0 mm Duplex Round	2	2.0	7 kg/km	50	30	30 mm	20 mm		
2.0 mm Simplex	1	2.0	5 kg/km	50	30	50 mm	30 mm		

FIBER PERFORMANCE

Fiber Type	Maximum Attenuation (dB/km)				Bandwidth (MHz*km)		Transmission Distance (meters)				
	850 nm	1300 nm	1310 nm	1550 nm	850 nm	1300 nm	100 Mb	1 GbE	10 GbE	40 GbE	100 GbE
8.2/125 µm Single-mode (OS2)	N/A	N/A	0.4	0.3	N/A	N/A	>5,000 @ 1310 nm		>10,000 @ 1310 nm	N/A	N/A
62.5/125 µm MM (OM1)	3.5	3.5	N/A	N/A	200	500	300/300 @ 850/1300 nm	300/600 @ 850/1300 nm	36/300 @ 850/1300 nm	N/A	N/A
50/125 µm LO (10G-300m) MM (OM3)	3.0	3.0	N/A	N/A	2,000*	500**		1,000/600 @ 850/1300 nm	300/300 @ 850/1300 nm	100 @ 850 nm	100 @ 850 nm
50/125 µm LO (10G-550m) MM (OM4)	3.0	3.0	N/A	N/A	4,700*	500**		1,040/600 @ 850/1300 nm	550/300 @ 850/1300 nm	150 @ 850 nm	150 @ 850 nm

*The effective modal bandwidth is determined based on an overfill launch (OFL) per ANSI/TIA-455-204, except on laser-optimized fiber types.

** 10GbE transmission @ 1,300 nm only applies to 10GBASE-LX4 (CWDM).



PRODUCT SPECIFICATIONS

VPC and LPC Fiber Patch Cords

OPTICAL SPECIFICATIONS

	Insertion Loss: Standard Performance	Insertion Loss: Low Loss	Return Loss
Single-Mode	≤ 0.25 dB	≤ 0.15 dB	UPC: ≥ 50 dB, APC: ≥ 60 dB
Multimode	≤ 0.25 dB	≤ 0.15 dB	≥ 26 dB

PART NUMBERS

	Fiber Type	Cable Type	Connectors	Color	Length (meters)
VPC-S2D1ACAC0010	SM OS2	1.6 mm Dup Zip	SC/APC - SC/APC	Yellow	1.0
VPC-S2D1ACAC0020	SM OS2	1.6 mm Dup Zip	SC/APC - SC/APC	Yellow	2.0
VPC-S2D1ACAC0030	SM OS2	1.6 mm Dup Zip	SC/APC - SC/APC	Yellow	3.0
VPC-S2D1ACAC0050	SM OS2	1.6 mm Dup Zip	SC/APC - SC/APC	Yellow	5.0
VPC-S2D1LCLC0010	SM OS2	1.6 mm Dup Zip	LC-LC	Yellow	1.0
VPC-S2D1LCLC0020	SM OS2	1.6 mm Dup Zip	LC-LC	Yellow	2.0
VPC-S2D1LCLC0030	SM OS2	1.6 mm Dup Zip	LC-LC	Yellow	3.0
VPC-S2D1LCLC0050	SM OS2	1.6 mm Dup Zip	LC-LC	Yellow	5.0
VPC-S2D1LCLC0100	SM OS2	1.6 mm Dup Zip	LC-LC	Yellow	10.0
VPC-S2D1LCSC0010	SM OS2	1.6 mm Dup Zip	LC-SC	Yellow	1.0
VPC-S2D1LCSC0020	SM OS2	1.6 mm Dup Zip	LC-SC	Yellow	2.0
VPC-S2D1LCSC0030	SM OS2	1.6 mm Dup Zip	LC-SC	Yellow	3.0
VPC-S2D1LCSC0100	SM OS2	1.6 mm Dup Zip	LC-SC	Yellow	10.0
VPC-S2D1SCSC0010	SM OS2	1.6 mm Dup Zip	SC-SC	Yellow	1.0
VPC-S2D1SCSC0020	SM OS2	1.6 mm Dup Zip	SC-SC	Yellow	2.0
VPC-S2D1ALAL0010	SM OS2	1.6 mm Dup Zip	LC/APC-LC/APC	Yellow	1.0
VPC-S2D1ALAL0050	SM OS2	1.6 mm Dup Zip	LC/APC-LC/APC	Yellow	5.0
VPC-S2D1ALAL0030	SM OS2	1.6 mm Dup Zip	LC/APC-LC/APC	Yellow	3.0
VPC-S2R2LULU0010	SM OS2	2.0 mm Dup Round	LC/UNI-LC/UNI	Yellow	1.0
VPC-M4D1LCLC0010	MM OM4	1.6 mm Dup Zip	LC-LC	Heather Violet	1.0
VPC-M4D1LCLC0020	MM OM4	1.6 mm Dup Zip	LC-LC	Heather Violet	2.0
VPC-M4D1LCLC0030	MM OM4	1.6 mm Dup Zip	LC-LC	Heather Violet	3.0
VPC-M4D1LCLC0050	MM OM4	1.6 mm Dup Zip	LC-LC	Heather Violet	5.0
VPC-M4D1LCLC0100	MM OM4	1.6 mm Dup Zip	LC-LC	Heather Violet	10.0
VPC-M4D1LCSC0020	MM OM4	1.6 mm Dup Zip	LC-SC	Heather Violet	2.0
VPC-M4D1LCSC0030	MM OM4	1.6 mm Dup Zip	LC-SC	Heather Violet	3.0
VPC-M4R2LULU0010	MM OM4	2.0 mm Dup Round	LC/UNI-LC/UNI	Heather Violet	1.0
VPC-M3D1LCLC0010	MM OM3	1.6 mm Dup Zip	LC-LC	Aqua	1.0
VPC-M3D1LCLC0020	MM OM3	1.6 mm Dup Zip	LC-LC	Aqua	2.0
VPC-M3D1LCLC0030	MM OM3	1.6 mm Dup Zip	LC-LC	Aqua	3.0
VPC-M3D1LCSC0010	MM OM3	1.6 mm Dup Zip	LC-SC	Aqua	1.0
VPC-M3D1LCSC0020	MM OM3	1.6 mm Dup Zip	LC-SC	Aqua	2.0
VPC-M3D1LCSC0030	MM OM3	1.6 mm Dup Zip	LC-SC	Aqua	3.0
VPC-M3D1LCSC0050	MM OM3	1.6 mm Dup Zip	LC-SC	Aqua	5.0
VPC-M3D1LCSC0100	MM OM3	1.6 mm Dup Zip	LC-SC	Aqua	10.0
VPC-M5D1LCLC0010	MM OM5	1.6 mm Dup Zip	LC-LC	Lime	1.0

PRODUCT SPECIFICATIONS

VPC and LPC Fiber Patch Cords

Make-to-order!		VPC AND LPC FIBER PATCH CORD OPTIONS				
Product Type	Fiber Type	Cable Type	Connector	Connector	Cable length (m)***	Customization
- VPC = Standard Fiber Patch Cord - LPC = Low Loss Fiber Patch Cord	- S2 = OS2 Yellow - M1 = OM1 Orange - M3 = OM3 Aqua - M4 = OM4 H. Violet - M5 = OM5 Lime	- S2 = 2.0 MM SIMPLEX - D0 = 1.2 MM DUP-ZIP* - D1 = 1.6 MM DUP-ZIP - R2 = 2.0 MM DUP-RND**	- LC = LC/UPC - LU=LC/UPC SPECTRO-LINK™ Unibody** - LP = LC/UPC/Uniboot** - AP = LC/APC/Uniboot** - L9 = LC/9APC - AL = LC/APC - SC = SC/UPC - AC = SC/APC - C9 = SC/9APC - ST = ST/UPC - FC = FC/UPC - AF = FC/APC	- LC = LC/UPC - LU=LC/UPC SPECTRO-LINK™ Unibody** - LP = LC/UPC/Uniboot** - AP = LC/APC/ Uniboot** - L9 = LC/9APC - AL = LC/APC - SC = SC/UPC - AC = SC/APC - C9 = SC/9APC - ST = ST/UPC - FC = FC/UPC - AF = FC/APC - XX = PTAIL	0005 = 000.5 Meters 0015 = 001.5 Meters 0150 = 015.0 Meters	Colors**** 01 = Blue 02 = Orange 03 = Green 04 = Brown 05 = Slate 06 = White 07 = Red 08 = Black 09 = Yellow 10 = Violet 11 = Rose 12 = Aqua Polarity - A = A-A



For assistance customizing your fiber patch cords, please visit Leviton.com/mto or call Tech Support +44 (0) 1592 778494.

Notes on configuring fiber patch cords:

* 1.2 mm duplex zip patch cords have a 2-km minimum order quantity.

** 2.0 mm duplex round patch cords require LC Unibody or uniboot type connectors. Leviton recommends LC Unibody (LU) connectors for use in applications with SFP+ or SFP28 transceivers that have pull tabs.

*** Length ≤ 30 metres are configurable in .2/.3/.4/.5/.6/.7/.8/.9 meter increments.

**** Patch cords with custom colors have a 2-km minimum order quantity.

G.657.A2 fiber is available upon request as a custom item and has a 2-km minimum order quantity.

For further support information, visit Leviton.com/ns/support

Page 4 of 4

USA
Network Solutions Headquarters
+1 (800) 722 2082
infoUSA@leviton.com

BERK-TEK™ Cable
+1 (800) 237 5835 | infoUSA@leviton.com

Asia Pacific
+852 3620 2602
infoAPAC@leviton.com

Canada
+1 (800) 461 2002
infoCanada@leviton.com

Europe
+44 (0) 1592 772124
infoEurope@leviton.com

Latin America
MX: +52 (55) 2128 6286
LATAM: +52 (55) 2333 5963
infoLATAM@leviton.com

Middle East & Africa
+971 (4) 247 9800
infoMEA@leviton.com

NETWORK SOLUTIONS PRODUCTS ARE AVAILABLE WORLDWIDE IN OVER 100 COUNTRIES. VISIT US ONLINE AT LEVITON.COM/NS TO LEARN MORE.