

**Special features**

- Including 0.5 m connecting cable
- Including honeycomb filter

<b>Housing Material</b>	Stainless steel	<b>Storage Temperature</b>	-10 to 60 °C
<b>Housing Color</b>	Silver	<b>IP Protection Class</b>	IP 67
<b>Housing Surface</b>	Brushed	<b>Load Force max.</b>	20 kN
<b>Protection Class</b>	Protection class I/protective grounding	<b>Life Time L70 / B50</b>	30000 h
<b>Rated Input</b>	29.1 W	<b>Switching Cycles</b>	100000
<b>Rated Input Voltage Frequency</b>	220-240 V/AC 50 / 60 Hz	<b>Power Consumption</b>	30 kWh/1000h
<b>Power Supply Unit incl.</b>	Yes	<b>Energy Efficiency Class</b>	G
<b>Connection Cable Primary</b>	Yes		
<b>Primary Connection</b>	Connection box		
<b>Primary Cable Length</b>	0.5 m		
<b>Dimmable</b>	No		
<b>Motion Detector</b>	No		
<b>Light Source</b>	LED, Light source not changeable		
<b>Color Temperature</b>	3000 K		
<b>Colour Consistency</b>	5 SDCM		
<b>Colour Rendering Index (Ra)</b>	80		
<b>Rated Luminous Flux</b>	1650 lm		
<b>Luminous Efficiency</b>	56.7 lm/W		
<b>Rated Angle of Reflection</b>	38 Degree		
<b>Distribution Characteristic 120°</b>	DLS		
<b>Light Exit Surfaces</b>	1		
<b>Light characteristics</b>	Direct		
<b>Light direction</b>	Top		
<b>Height</b>	190 mm		
<b>Diameter</b>	250 mm		
<b>Installation Depth</b>	220 mm		
<b>Cut Out Diameter</b>	222 mm		
<b>Product weight</b>	4268 g		
<b>Working Temperature</b>	-20 to 40 °C		