



SCULPTORIS series pendant lamps boast an impressive matte visual design and luminous ring. With high luminous intensity and large light emission angle, the series offers flexible applications in many different areas, whether in living areas or for providing imposing lighting solutions to office spaces.

#### Special features

- Light colour adjustable in 2 stages
- Uniform illumination
- Circumferential diffuser
- Suspended mounting up to 1,800 mm

<b>Housing Material</b>	Aluminium	<b>Working Temperature</b>	-10 to 45 °C
<b>Housing Color</b>	Black	<b>Storage Temperature</b>	-10 to 45 °C
<b>Housing Surface</b>	Matt	<b>IP Protection Class</b>	IP 20
<b>Material of Lens</b>	Acryl	<b>Life Time L70 / B50</b>	30000 h
<b>Surface Structure of Lens</b>	Satined	<b>Switching Cycles</b>	20000
<b>Protection Class</b>	Protection class I/protective grounding	<b>Power Consumption</b>	42 kWh/1000h
<b>Rated Input</b>	42 W	<b>Energy Efficiency Class Lightsource</b>	This product contains a light source of energy efficiency class E.
<b>Rated Input Voltage Frequency</b>	220-240 V/AC 50 / 60 Hz		
<b>Power Supply Unit incl.</b>	Yes		
<b>Connection Type</b>	Clamp		
<b>Dimmable</b>	Yes		
<b>Control technology</b>	Leading-edge dimmer, Trailing-edge dimmer		
<b>Motion Detector</b>	No		
<b>Light Source</b>	LED, Light source changeable TC		
<b>Color Temperature</b>	3000/4000 K		
<b>Colour Consistency</b>	6 SDCM		
<b>Colour Rendering Index (Ra)</b>	80		
<b>Rated Luminous Flux</b>	3000/3100 lm		
<b>Rated Luminous Flux 2</b>	3100 lm		
<b>Rated Angle of Reflection</b>	150 Degree		
<b>Light Distribution</b>	Symmetric		
<b>Light Exit Surfaces</b>	1		
<b>Light characteristics</b>	Direct, Indirect		
<b>Light direction</b>	Top, Below		
<b>Height</b>	110 mm		
<b>Diameter</b>	600 mm		
<b>Base height</b>	65 mm		
<b>Base diameter</b>	220 mm		
<b>Pendulum Length max.</b>	1800 mm		