



#### Product Features

25/10 Gigabit-Patchpanel with 24 universal modules UM-Cat.6A iso 25/10G, 19"/1 U, direct mounting, light grey (similar RAL 7035)

- for use in 25-Gigabit-Ethernet Networks (bandwidth 1250 MHz)
- for use in 10-Gigabit-Ethernet Networks (bandwidth 500 MHz)
- 19"/1 U, direct mounting
- labelled ports (1-24)
- additional strain relief possibility for data cables with cable ties
- performance universal modular jack:
  - 25GB universal modular jack, shielded, for standard Keystone openings
  - 1 x RJ45 jack
  - for standard keystone cutouts (14,8 x 19,3mm)
  - zinc diecast design
  - nickel plated housing
  - suitable for cables with 6-10 mm diameter
  - solid wires: IDC-terminals for one wire 0,57-0,64 mm diameter
  - 1 wire for each contact, reconnectable 4-times (at the same or larger diameter)
  - shield contact regarding to standards
  - defined grounding via flat plug possible
  - easy to mount (2 pieces)
  - built-in dust protection (removable)
  - colour code T568A and T568B according to TIA/EIA-568 B.2
  - suitable für PoE+ (Power over Ethernet) according to IEEE 802.3at
  - UPOE conform
  - HDBaseT conform
  - according to the following standards for 25Gbit:
    - ISO/IEC TR 11801-9905
    - ISO/IEC 11801, Class I bis 1250 MHz, shielded
  - according to the following standards for 10Gbit:
    - ISO/IEC 11801, Cat.6A, shielded
    - DIN EN 50173-1, Cat.6A, shielded
    - ANSI TIA/EIA-568-C2 Category 6A
    - DIN EN 60603-7-51, 500 MHz, shielded
  - life > 750 cycles
  - GHMT certified

Features	
General	
Surface	laminated
shielded	Yes
PoweroverEthernet	Yes
Protection class IP	20
Statistical goods number	85369010
Country of manufacture	DE
GTIN (EAN)	4043921666784
Mounting types	
(19-inch)-installation, 1 rack unit	Yes
Dimensions/Weights without packaging	
Net weight piece kg	1,305
Certifications	
GHMT	Yes
CE	Yes
RoHS conform	Yes
Logistics Information	
Packaging	box
Packaging unit Quantity	1
Packaging unit Weight kg	1,498
Packaging unit Width mm	510
Packaging unit Height mm	150
Packaging unit Depth mm	55
References	
Accessories	39200002, 39200003, 39200012

