

Panel mounting socket outlet, angled TN - flange 114x114, fixing centers 90x90



| Product description | |
|---------------------------|---|
| BALS-Prd.-Nr | 120036 |
| EAN | 4024941108102 |
| Product category | TN panel mounting socket outlet, angled |
| Current | 63A |
| Number of poles | 4p |
| Poles | 3P+PE |
| Position of earth contact | 11 h |
| Voltage | 440 up to 460V, mainly for ship installations |

| Product description | |
|--------------------------------|--|
| Frequency | 60Hz |
| VG-Type-No.: | VG 96919 BS 031 |
| Protection degree | IP67 |
| Colour code | bronze-green RAL 6031-F9 |
| Colour of appliance | Bayonet ring bronze-green RAL 6031-F9, Hinged lid bronze-green RAL 6031-F9, Enclosure bronze-green RAL 6031-F9 |
| Connection design | screw terminal as box terminal with Kontex-contact |
| Maximum conductor size | 25.0 qmm |
| Cable entry | other |
| Height | 124mm |
| Width | 114mm |
| Depth | 144mm |
| Flange size vertical | 114mm |
| Flange size horizontal | 114mm |
| Drill hole distance vertical | 90mm |
| Drill hole distance horizontal | 90mm |
| Material of enclosure | Polyamide |
| Contact | The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated |

| Additional technical properties | |
|---------------------------------|--|
| | with pilot contact, The inclination is 15° |

| Additional technical properties | |
|---------------------------------|-----------------------------|
| | With bayonet cover on strap |

| Logistics data | |
|----------------|----------------|
| Weight/pcs | 0.0 kg / Piece |
| Packaging | Bag |
| Content amount | 1 ST |
| EAN | 4024941108102 |
| Length | 144 mm |
| Width | 114 mm |
| Height | 124 mm |
| Weight | 0.001 kg |
| Volume | 2,035.584 ccm |
| Packaging | Carton |
| Content amount | 5 ST |
| EAN | 4024941838801 |
| Length | 295 mm |
| Width | 185 mm |
| Height | 215 mm |
| Weight | 0.164 kg |
| Volume | 9,975 ccm |



| Ampere | 63 | 63 | 63 | 125 | 125 | 125 |
|----------------------------|-------|-------|-------|-------|-------|-------|
| Polzahl | 3 | 4 | 5 | 3 | 4 | 5 |
| a | 114,0 | 114,0 | 114,0 | 114,0 | 114,0 | 114,0 |
| b | 114,0 | 114,0 | 114,0 | 114,0 | 114,0 | 114,0 |
| c | 90,0 | 90,0 | 90,0 | 90,0 | 90,0 | 90,0 |
| d | 90,0 | 90,0 | 90,0 | 90,0 | 90,0 | 90,0 |
| e ø | 5,5 | 5,5 | 5,5 | 6,5 | 6,5 | 6,5 |
| f | 12,0 | 12,0 | 12,0 | 12,0 | 12,0 | 12,0 |
| h | 65,0 | 65,0 | 65,0 | 82,0 | 82,0 | 82,0 |
| i | 82,0 | 82,0 | 82,0 | 90,0 | 90,0 | 90,0 |
| k | 92,0 | 92,0 | 92,0 | 92,0 | 92,0 | 92,0 |
| l | 92,0 | 92,0 | 92,0 | 105,0 | 105,0 | 105,0 |
| α | 15° | 15° | 15° | 15° | 15° | 15° |
| Leiter mm ² min | 6,0 | 6,0 | 6,0 | 25,0 | 25,0 | 25,0 |
| Leiter mm ² max | 25,0 | 25,0 | 25,0 | 70,0 | 70,0 | 70,0 |