

**Special features**

- Including 1 m connecting cable
- Including honeycomb filter

<b>Housing Material</b>	Stainless steel, Die-cast aluminium
<b>Housing Color</b>	Silver
<b>Material of Lens</b>	Glass
<b>Protection Class</b>	Protection class I/protective grounding
<b>Rated Input</b>	9.3 W
<b>Rated Input Voltage Frequency</b>	220-240 V/AC 50 / 60 Hz
<b>Power Supply Unit incl.</b>	Yes
<b>Connection Cable Primary</b>	Yes
<b>Primary Connection</b>	Connection box
<b>Primary Cable Length</b>	1 m
<b>Dimmable</b>	No
<b>Motion Detector</b>	No

<b>Light Source</b>	LED, Light source not changeable
<b>Color Temperature</b>	3000 K
<b>Colour Consistency</b>	5 SDCM
<b>Colour Rendering Index (Ra)</b>	80
<b>Rated Luminous Flux</b>	480 lm
<b>Luminous Efficiency</b>	51.6 lm/W
<b>Rated Angle of Reflection</b>	17 Degree
<b>Light Distribution</b>	Symmetric
<b>Distribution Characteristic 120°</b>	DLS

<b>Swivel Angle</b>	30 Degree
<b>Light Exit Surfaces</b>	1
<b>Light characteristics</b>	Direct
<b>Light direction</b>	Top

<b>Height</b>	128 mm
<b>Diameter</b>	173 mm
<b>Installation Depth</b>	220 mm
<b>Cut Out Diameter</b>	155 mm
<b>Product weight</b>	2466 g

<b>Working Temperature</b>	-20 to 40 °C
<b>Storage Temperature</b>	-10 to 60 °C
<b>IP Protection Class</b>	IP 67
<b>IK Protection Class</b>	IK10
<b>Load Force max.</b>	20 kN
<b>Life Time L70 / B50</b>	35000 h
<b>Switching Cycles</b>	20000
<b>Power Consumption</b>	10 kWh/1000h
<b>Energy Efficiency Class</b>	G