

15p STR FE PL2_4-40 nut_Reel_140 pcs



| Part number | 09 55 215 6612 741 |
|--------------------|--|
| Specification | 15p STR FE PL2_4-40 nut_Reel_140 pcs |
| HARTING eCatalogue | https://b2b.harting.com/09552156612741 |

Image is for illustration purposes only. Please refer to product description.

Identification

| Category | Connectors |
|----------------------------|---------------------|
| Series | D-Sub |
| Identification | Standard |
| Element | Connector |
| Description of the contact | Stamped Straight |

Version

| Termination method | Reflow soldering termination (SMT) |
|--------------------|---------------------------------------|
| Gender | Female |
| Size | D-Sub 2 |
| Connection type | Motherboard to daughtercard Mezzanine |
| Number of contacts | 15 |
| Locking type | Fixing flange with thread 4-40 UNC |
| Pack contents | 140 pieces on reel |

Technical characteristics

| Contact spacing (termination side) | 2.74 mm |
|------------------------------------|-------------------------|
| Rated current | 5 A |
| Clearance distance | ≥1 mm |
| Creepage distance | ≥1 mm |
| Insulation resistance | > 5 x 10 ⁹ Ω |
| Contact resistance | ≤25 mΩ |



Technical characteristics

| Tightening torque | ≤0.6 Nm Female screw lock |
|----------------------------------|---|
| Limiting temperature | -55 +125 °C (during reflow soldering max. +240 °C for 30 s) |
| Insertion force | ≤50 N |
| Withdrawal force | ≥4.5 N ≤33 N |
| Performance level | 2 acc. to CECC 75301-802 |
| Mating cycles | ≥250 |
| Test voltage U _{r.m.s.} | 1 kV |
| Isolation group | IIIa (175 ≤ CTI < 400) |
| PCB thickness | ≥1.6 mm |
| Installation height | 6.35 mm |
| Hot plugging | No |
| Moisture Sensitivity Level (MSL) | 1 acc. to ECA/IPC/JEDEC J-STD-020D |
| Process Sensitivity Level (PSL) | R0 acc. to ECA/IPC/JEDEC J-STD-020D |

Material properties

| iquid crystal polymer (LCP) Shell: steel, nickel plated |
|---|
| Black |
| Copper alloy |
| Noble metal over Ni |
| /-0 |
| compliant |
| compliant |
| |
| Not contained |
| Not contained |
| Not contained |
| Not contained |
| |

Specifications and approvals

Specifications DIN 41652



Specifications and approvals

| UL / CSA | UL 1977 ECBT2.E102079 |
|----------|-----------------------------------|
| OL / CSA | CSA-C22.2 No. 182.3 ECBT8.E102079 |

Commercial data

| Packaging size | 1 |
|--------------------------------|------------------------|
| Net weight | 1,600 g |
| Country of origin | China |
| European customs tariff number | 85366990 |
| GTIN | 5713140069251 |
| eCl@ss | 27440214 D-Sub coupler |