

Wall mounting socket outlet, fused - housing dimensions 260x160, with fuse base D 02



Product description	
BALS-Prd.-Nr	15083
EAN	4024941150835
product category (PG)	TE wall mounting socket outlet, fused
current (A)	63A
number of poles (P99)	4p
number of poles (P)	3P+PE
position of earth contact (H)	6 h
voltage (V)	380 up to 415V

Product description	
frequency (HZ)	50 and 60Hz
protection degree (SA)	IP67
colour code 1 (KF1)	red RAL 3000
Colour of appliance	Operating window smoky topaz, Hinged lid red RAL 3000, Bayonet ring grey RAL 7035, Housing screws grey RAL 7035, Housing bottom grey RAL 7035, Housing top grey RAL 7035
connection design (AT)	screw terminal as box terminal with Kontex-contact
maximum conductor size (LQ)	25.0 qmm
cable entry (KE)	top entry M40 bottom entry M40/M32
Height	304mm
Width	160mm
Depth	195mm
dimension of enclosure (GG)	260x160 mm (HxW)
material of enclosure (GM)	Polycarbonate
contact	The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated

Additional technical properties	
	The cable entry is one at top and two at bottom open
	With fuse base 3 pole D02

Logistics data	
Weight/pcs	0.0 kg / Piece

Logistics data	
Packaging	Carton
Content amount	1 ST
EAN	4024941150835
Length	325 mm
Width	217 mm
Height	210 mm
Weight	0.212 kg
Volume	13,588.4 ccm



14 MB 11

Ampere	32	32	63	63			
Polzahl	4	5	4	5			
a	160,0	160,0	160,0	160,0			
b	260,0	260,0	260,0	260,0			
c	140,0	140,0	140,0	140,0			
d	240,0	240,0	240,0	240,0			
e	172,0	174,0	195,0	195,0			
f	293,0	294,0	304,0	304,0			
g ø	8,1	8,1	8,1	8,1			
h	10,0	10,0	10,0	10,0			
i	M40	M40	M40	M40			
k	M32/40	M32/40	M32/40	M32/40			