



Whilst flat surfaces and covers are the go-to for most surface-mounted ceiling lights, the ZANIAH places special emphasis on its 360° lamp [either a 12W, 18W or 21W variant]. This isn't just for visual reasons, as the ZANIAH can be combined with covers from the similarly new ORBIT series if needed. This means that not only are different colours available - the ZANIAH itself comes in eight colour variants per performance class.

**Special features**

- 360° light emission angle
- Dimmable

<b>Housing Material</b>	Aluminium	<b>Switching Cycles</b>	25000
<b>Housing Color</b>	Yellow	<b>Power Consumption</b>	18 kWh/1000h
<b>Material of Lens</b>	Plastic	<b>Energy Efficiency Class</b>	G
<b>Protection Class</b>	Protection class II/protective insulation		
<b>Rated Input</b>	18 W		
<b>Rated Input Voltage Frequency</b>	220-240 V/AC 50 / 60 Hz		
<b>Power Supply Unit incl.</b>	Yes		
<b>Connection Type</b>	Clamp		
<b>Dimmable</b>	Yes		
<b>Control technology</b>	Leading-edge dimmer, Trailing-edge dimmer		
<b>Motion Detector</b>	No		
<b>Light Source</b>	LED, Light source not changeable		
<b>Color Temperature</b>	3000 K		
<b>Colour Consistency</b>	6 SDCM		
<b>Colour Rendering Index (Ra)</b>	80		
<b>Rated Luminous Flux</b>	2020 lm		
<b>Rated Angle of Reflection</b>	120 Degree		
<b>Distribution Characteristic 120°</b>	NDLS		
<b>Light Exit Surfaces</b>	2		
<b>Light characteristics</b>	Direct, Indirect		
<b>Light direction</b>	Below, Rear		
<b>Height</b>	46 mm		
<b>Diameter</b>	370 mm		
<b>Working Temperature</b>	-20 to 45 °C		
<b>Storage Temperature</b>	-10 to 60 °C		
<b>IP Protection Class</b>	IP 20		
<b>IK Protection Class</b>	IK05		
<b>Life Time L70 / B50</b>	50000 h		