



Despite the linear design, the Wallwasher - CAPH series assortment is well-rounded. Wallwashers offer a variety of options to accentuate different objects. Whether a rustic stone wall in warm 3,000 K or a modern new build in RGBW. The different visual designs with symmetrical or asymmetrical diffusion angles help with positioning.

With the 230 V variants, no further accessories are required. Thanks to the 24 V versions, the CAPH Wallwashers can be connected to all variants of the control unit on the market.

**Special features**

- Including connecting cable

<b>Housing Material</b>	Die-cast aluminium
<b>Housing Color</b>	Grey
<b>Material of Lens</b>	Glass
<b>Protection Class</b>	Protection class I/protective grounding
<b>Rated Input</b>	38 W
<b>Rated Input Voltage</b>	220-240 V/AC 50 / 60 Hz
<b>Frequency</b>	
<b>Power Supply Unit incl.</b>	Yes
<b>Connection Cable Primary</b>	Yes
<b>Primary Connection</b>	Power plug IP44
<b>Primary Cable Length</b>	2 m
<b>Connection Type According to Standard</b>	Typ Y
<b>Dimmable</b>	No
<b>Motion Detector</b>	No

<b>Working Temperature</b>	-20 to 60 °C
<b>Storage Temperature</b>	-20 to 60 °C
<b>IP Protection Class Lamp</b>	IP 65
<b>IP Protection Class Plug</b>	IP 44
<b>Life Time L70 / B50</b>	30000 h
<b>Switching Cycles</b>	100000
<b>Power Consumption</b>	38 kWh/1000h
<b>Energy Efficiency Class</b>	G

<b>Light Source</b>	LED, Light source not changeable
<b>Color Temperature</b>	3000 K
<b>Colour Consistency</b>	6 SDCM
<b>Colour Rendering Index (Ra)</b>	80
<b>Rated Luminous Flux</b>	2580 lm
<b>Rated Angle of Reflection</b>	40 Degree
<b>Rated Angle of Reflection 2</b>	15 Degree
<b>Light Distribution</b>	Asymetric
<b>Distribution Characteristic 120°</b>	DLS

<b>Light Exit Surfaces</b>	1
<b>Light characteristics</b>	Direct
<b>Light direction</b>	Top

<b>Length</b>	1000 mm
<b>Width</b>	53.36 mm
<b>Height</b>	81.07 mm