



Special features

- High IP protection
- High colour reproduction value

Housing Material	Die-cast aluminium
Housing Color	White
Protection Class	Protection class III/safety extra-low voltage
Operating Mode	Constant current
Rated Input	6.5 W
Rated Input Voltage	17-18 V/DC
Rated Current	350 mA
Power Supply Unit incl.	No
Connection Cable Secondary	Yes
Secondary Connection	Open cables
Secondary Cable Length	0.4 m
Dimmable	Yes
Control technology	Dimmable via optional power supply unit
Motion Detector	No

Product weight	178 g
Working Temperature	-5 to 40 °C
Storage Temperature	-10 to 60 °C
IP Protection Class	IP 65
Life Time L70 / B50	30000 h
Switching Cycles	100000
Power Consumption	7 kWh/1000h
Energy Efficiency Class	G

Light Source	LED, Light source not changeable
Color Temperature	2700 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	670 lm
Luminous Efficiency	103.1 lm/W
Rated Angle of Reflection	45 Degree
Light Distribution	Symmetric
Distribution Characteristic 120°	DLS

Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below

Height	44 mm
Diameter	78 mm
Installation Depth	46 mm
Cut Out Diameter	68 mm