



<b>Housing Material</b>	Aluminium
<b>Housing Color</b>	White
<b>Housing Surface</b>	Matt
<b>Material of Lens</b>	Polycarbonate - PC
<b>Protection Class</b>	Protection class II/protective insulation
<b>Rated Input</b>	28 W
<b>Rated Input Voltage Frequency</b>	200-240 V/AC 50 / 60 Hz
<b>Power Supply Unit incl.</b>	Yes
<b>Connection Type</b>	Adapter
<b>Dimmable</b>	No
<b>Motion Detector</b>	No

<b>IP Protection Class</b>	IP 20
<b>Life Time L70 / B50</b>	43800 h
<b>Switching Cycles</b>	50000
<b>Power Consumption</b>	28 kWh/1000h
<b>Energy Efficiency Class</b>	E

<b>Light Source</b>	LED, Light source not changeable
<b>Lightcolor</b>	Neutral white
<b>Color Temperature</b>	4000 K
<b>Colour Consistency</b>	6 SDCM
<b>Colour Rendering Index (Ra)</b>	80
<b>Rated Luminous Flux</b>	3400 lm
<b>Luminous Efficiency</b>	121.4 lm/W
<b>Rated Angle of Reflection</b>	110 Degree
<b>Distribution Characteristic 120°</b>	DLS

<b>Light Exit Surfaces</b>	1
<b>Light characteristics</b>	Direct
<b>Light direction</b>	Below

<b>Length</b>	1087 mm
<b>Width</b>	62 mm
<b>Height</b>	32 mm
<b>Product weight</b>	745 g

<b>Working Temperature</b>	-25 to 45 °C
<b>Storage Temperature</b>	-25 to 50 °C