



Special features

- UGR less than 19
- Dimmable using controller
- Light colour adjustable using controller

Housing Material	Aluminium
Housing Color	White
Material of Lens	PMMA
Protection Class	Protection class III/safety extra-low voltage
Operating Mode	Constant voltage
Rated Input	77 W
Rated Input Voltage	24 V/DC
Power Supply Unit incl.	No
Connection Cable Secondary	Yes
Secondary Connection	Open cables
Dimmable	Yes
Control technology	Dimmable via optional controller
Motion Detector	No

Working Temperature	-20 to 40 °C
Storage Temperature	-30 to 60 °C
IP Protection Class	IP 20

Life Time L70 / B50	30000 h
Switching Cycles	15000
Power Consumption	77 kWh/1000h
Energy Efficiency Class	G

Light Source	LED, Light source not changeable
Colour Temperature	3000-4000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	6655 lm
Luminous Efficiency	86.4 lm/W
Rated Angle of Reflection	120 Degree
UGR	19
Distribution Characteristic 120°	DLS

Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below

Length	1195 mm
Width	295 mm
Height	10 mm
Product weight	3060 g

