

Datenblatt Art. 350.000

Data sheet | Fiche technique | Scheda tecnica | Fișa tehnică

PRIMO 2 Steckdosenleiste

Elektrische Kenngrößen		Electrical parameters	
Nennstrom / Bemessungsspannung	16A / 250V~	Rated current / rated voltage	16A / 250V~
Frequenz	50Hz	Frequency	50Hz
Netzanschluss		Power supply	
Zuleitung	2,0m H05VV-F 3G1,5mm ²	Supply cable	2,0m H05VV-F 3G1,5mm ²
Farbe Zuleitung	Schwarz	Colour supply cable	Black
Wiederanschließbar		Rewirable	
Stecker	CEE 7/7 (Type E/F)	Plug	CEE 7/7 (Type E/F)
Steckertyp	Winkelstecker	Plug type	Right angled plug
Stromausgang		Power output	
Steckdosen		Socket outlets	
6x CEE 7/3 (Type F)		6x CEE 7/3 (Type F)	
2-polig mit Schutzkontakt		2-pole with earthing contact	
Mit erhöhtem Berührungsschutz		With shutter	
Schwarz, ähnlich RAL 9005, 35°		Black, similar to RAL 9005, 35°	
16A / 250V~, IP20		16A / 250V~, IP20	
Weitere Produkteigenschaften		Further product attributes	
Plattform	Standard (kHE)	Plattform	Standard (kHE)
Material		Material	
Gehäuse:		Housing:	
Aluminium, eloxiert schwarz, ähnlich RAL 9005		Aluminium, anodised black, similar to RAL 9005	
Schwarze Design-Endkappen		Black design endcaps	
Abdeckung:		Cover:	
PA6 GF30 850°C, schwarz ähnlich RAL 9005		PA6 GF30 850°C, black similar to RAL 9005	
Lieferumfang		Scope of delivery	
1x PRIMO 2 Steckdosenleiste		1x PRIMO 2 power strip	
Im Karton		In carton	

Umgebungsbedingungen		Environmental conditions	
----------------------	--	--------------------------	--

Maximale Höhe	0 - 2000m	Maximum height	0 - 2000m
Umgebungstemperatur bei Montage und Nutzung	5°C – 35°C	Surrounding temperature during mounting and use	5°C – 35°C
Vor direkter Sonneneinstrahlung schützen.		Protect from direct sunlight.	
Umgebungstemperatur bei Transport und Lagerung	-25°C - 60°C	Surrounding temperature during transport and storage	-25°C - 60°C
Relative Luftfeuchtigkeit (nicht kondensierend)	5 – 95%	Relative humidity (non-condensin	5 – 95%
Schutzart	IP20	Protection type	IP20

Konformität		Conformity	
-------------	--	------------	--

Bauart geprüft	DIN VDE 0620-1 / DIN 49440 / CEE 7/3	Type approved	DIN VDE 0620-1 / DIN 49440 / CEE 7/3
-----------------------	--------------------------------------	----------------------	--------------------------------------

