



09670500446	50	42	61,1	69	55	19,5	6-14	56,2	57,8	15	52,6	54,7	55,7	40,2	21	4,1
09670370446	37	44,4	63,5	71,4	55	18,9	6-13	58,6	57,8	12,1	55	57,2	58,1	38,4	21	3,9
09670250446	25	28	47	54,9	52	16,2	4-12	42,1	54,8	11,6	38,2	40,5	41,4	32,8	18	3,9
09670150446	15	16	33,3	41,2	45	16,2	4-11	28,4	47,8	11,6	24,8	26,9	27,9	26,3	18	3,9
09670090446	09	10	25	31,8	39,2	16,7	4-11	20	41,6	13,2	17	19	20	25,3	14	3,9
Part number	No. of contacts	A±0,3	B±0,1	C±0,3	D±0,3	E±0,3	F min.-max.	G±0,3	H±0,3	J±0,3	K±0,3	L±0,3	M±0,3	N±0,3	P±0,3	Q

ØF = Cable diameter

max. torque are 40 Ncm  
Hood is snapped together  
part- No. 3,4,5,6 and 8 not mounting

	All rights reserved		Created by ZHUANGJ		Inspected by LUOK		Standardisation 302077		Date 2020-10-20		State Final Release	
	Department EL PD		Title D-Sub 25-pole top entry plastic metallized		Doc-Key / ECM-Nr. 100873338/UGD/000/B 500000181594		Type TB		Number 09670XX0446		Rev. B	
HARTING Electronics GmbH		D-32339 Espelkamp								Page 1/1		