



Part no.	Ø	Wire gauge		Stripping length	Recommended crimping tools			
		mm ²	AWG		09 99 000 0888	09 99 000 0001	09 99 000 0110	09 99 000 0021
09 15 000 6227SP	0,90	0,14-0,37	26-22	8	X	X		
09 15 000 6224SP							X	X
09 15 000 6223SP	1,10	0,5	20		X	X	X	X
09 15 000 6225SP	1,30	0,75	18		X	X	X	X
09 15 000 6222SP	1,45	1	18		X	X	X	X
09 15 000 6221SP	1,75	1,5	16		X	X	X	X
09 15 000 6226SP	2,25	2,5	14	6	X	X		

		All Dimensions in mm Original Size DIN A4		Scale 2:1	Free size tol.		Ref.	
							Sub.	
		All rights reserved		Created by SPRENB	Inspected by RIEPE	Standardisation 302077	Date 2020-11-11	State Final Release
		Department EL PD						
HARTING Electric GmbH & Co. KG D-32339 Espelkamp		Title Han D-SMC-FC-CRT-Au-spec.						Doc-Key / ECM-Nr. 100109246/UGD/005/A 500000183173
		Type TB	Number 09150006201 09150006221SP 09150006222SP 09150006223SP					Page 1/1

Note: position of the inspection hole is on the crimp collar for 2.5mm² female contacts