



Housing Material	Die-cast aluminium
Housing Color	Grey
Material of Lens	Glass
Protection Class	Protection class III/safety extra-low voltage
Operating Mode	Constant voltage
Rated Input	5 W
Rated Input Voltage	5 V/DC
Power Supply Unit incl.	No
Connection Type	Micro-USB
Dimmable	Yes
Control technology	Touch-Sensor
Motion Detector	No
Accumulator/Battery Operated	Yes
Rechargeable/battery included	Yes
Number of Accumulator/Battery	1
Type of Accumulator/Battery	Li-Ion battery type 18650
Accumulator/Battery Capacity	7800 mAh
Accumulator/Battery Voltage	3.7 V/DC
Accumulator Charging Time	6-8 h
Accumulator Operating Time	6 h

Light Source	LED, Light source not changeable
Lightcolor	Warm white (WW)
Color Temperature	3000 K
Colour Rendering Index (Ra)	80
Rated Luminous Flux	460 lm
Luminous Efficiency	92 lm/W
Rated Angle of Reflection	120 Degree
Light Distribution	Symmetric
Distribution Characteristic 120°	NDLS

Light Exit Surfaces	1
Light characteristics	Direct

Light direction	Top
Length	180 mm
Width	180 mm
Height	267 mm
Base length	145 mm
Base width	145 mm
Base height	25 mm
Product weight	2370 g
Working Temperature	-10 to 45 °C
Storage Temperature	-10 to 45 °C
IP Protection Class	IP 54
Life Time L70 / B50	30000
Power Consumption	3 kWh/1000h