



Matching SLIM series pendant lamps are available for the current track system. The light body in die-cast aluminium is always the same size (300 x 39 mm). The pendant lamps for current tracks allow suspended mounting up to max. 180 cm.

The single-luminaire SLIM current track light therefore is especially well suited to gastronomy and retail projects with variable room layouts. The value of the Slim series is rounded off with a flexible fabric cable.



Special features

- Die-cast aluminium
- Fabric cable
- Particularly glare-free thanks to low UGR value
- Suspended mounting up to 1800 mm

Housing Material	Aluminium	Pendulum Length max.	1500 mm
Housing Color	White	Product weight	476 g
Colour of Lens	Transparent	Working Temperature	-20 to 45 °C
Surface Structure of Lens	Structured	Storage Temperature	-20 to 65 °C
Protection Class	Protection class I/protective grounding	IP Protection Class	IP 20
Rated Input	5 W	Life Time L70 / B50	50000 h
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz	Switching Cycles	100000
Power Supply Unit incl.	Yes	Power Consumption	5 kWh/1000h
Connection Type	Adapter	Energy Efficiency Class Lightsource	This product contains a light source of energy efficiency class E.
Dimmable	Yes		
Control technology	Leading-edge dimmer, Trailing-edge dimmer		
Motion Detector	No		
Light Source	LED, Light source changeable TC		
Lightcolor	Warm white (WW)		
Color Temperature	2700 K		
Colour Consistency	3 SDCM		
Colour Rendering Index (Ra)	90		
Rated Luminous Flux	500 lm		
Luminous Efficiency	100 lm/W		
Rated Angle of Reflection	24 Degree		
UGR	19		
Light Distribution	Symmetric		
Distribution Characteristic 120°	DLS		
Light Exit Surfaces	1		
Light characteristics	Direct		
Light direction	Below		
Length	1800 mm		
Height	300 mm		
Diameter	39 mm		