

Han EMC/B 6 Protect Cover metal



Image is for illustration purposes only. Please refer to product description.

| | |
|--------------------|---|
| Part number | 09 62 806 5425 |
| Specification | Han EMC/B 6 Protect Cover metal |
| HARTING eCatalogue | https://b2b.harting.com/09628065425 |

Identification

| | |
|-----------------------------|-------------------------------|
| Category | Accessories |
| Series of hoods/housings | Han [®] EMC/B |
| Type of hood/housing | Protection cover |
| Description of hood/housing | for bulkhead mounted housings |
| | for surface mounted housings |
| | Metal |
| Type | With fixing cord |
| | Low construction |
| | High construction |

Version

| | |
|--------------|--|
| Size | 6 B |
| Locking type | Single locking lever |
| Details | Not suitable for housings with external seals. |

Technical characteristics

| | |
|--|-----------------|
| Limiting temperature | -40 ... +125 °C |
| Degree of protection acc. to IEC 60529 | IP65 |
| Type rating acc. to UL 50 / UL 50E | 4 |
| | 12 |

Material properties

| | |
|-------------------------|--------------------|
| Material (hood/housing) | Aluminium die-cast |
| Surface (hood/housing) | Uncoated |
| Colour (hood/housing) | Unpainted |



Pushing Performance
Since 1945

Material properties

| | |
|--------------------------------------|----------------|
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | e |
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Not contained |
| California Proposition 65 substances | Yes |
| California Proposition 65 substances | Lead Nickel |

Specifications and approvals

| | |
|-----------|--|
| Approvals | DNV GL |
| UL / CSA | UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076 |

Commercial data

| | |
|--------------------------------|--|
| Packaging size | 1 |
| Net weight | 43.9 g |
| Country of origin | Germany |
| European customs tariff number | 85389099 |
| GTIN | 5713140191891 |
| eCl@ss | 27440208 Cap for industrial connectors |