



**Special features**

- Max. suspended mounting 1,200 mm
- Concrete housing
- Exchangeable lamp (GU10)

|                                      |   |
|--------------------------------------|---|
| <b>Housing Material</b>              | Concrete                                  |
| <b>Housing Color</b>                 | Grey                                      |
| <b>Housing Surface</b>               | Matt                                      |
| <b>Protection Class</b>              | Protection class II/protective insulation |
| <b>max. Power</b>                    | 1x max. 35 W                              |
| <b>Rated Input Voltage Frequency</b> | 220-240 V/AC 50 / 60 Hz                   |
| <b>Socket Description</b>            | GU10                                      |
| <b>Socket Quantity</b>               | 1   |
| <b>Connection Type</b>               | Clamp                                     |
| <b>Dimmable</b>                      | Yes                                       |
| <b>Control technology</b>            | Dimmable via optional light source        |
| <b>Motion Detector</b>               | No  |
| <b>Execution</b>                     | Without lamp                              |
| <b>Light Exit Surfaces</b>           | 1   |
| <b>Light characteristics</b>         | Direct                                    |
| <b>Light direction</b>               | Below                                     |
| <b>Length</b>                        | 70 mm                                     |
| <b>Width</b>                         | 70 mm                                     |
| <b>Height</b>                        | 250 mm                                    |
| <b>Base length</b>                   | 80 mm                                     |
| <b>Base width</b>                    | 80 mm                                     |
| <b>Base height</b>                   | 30 mm                                     |
| <b>Pendulum Length max.</b>          | 1450 mm                                   |
| <b>Product weight</b>                | 1847 g                                    |
| <b>Working Temperature</b>           | -5 to 40 °C                               |
| <b>Storage Temperature</b>           | -10 to 60 °C                              |
| <b>IP Protection Class</b>           | IP 20                                     |