

recessed ceiling spot

Artikel-Nr. 1928.05

Licht.
Für Generationen.

Entwurf

**Tender**

recessed ceiling spot, gold, round. In a compact design, for installation in tool-less rapid assembly systems Lamp holder: GX5.3, Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Steel, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Voltage: 12V, Power: 50W, Amount of light sources / fittings: 1.0 Qty, Adjustability: Pivoted, With control gear: No, Control: Other.

Article data	
Artikel-Nr.	1928.05
GTIN	4250047724742
Kurzbeschreibung	recessed ceiling spot
Material	Steel
Colour	Gold
Type of surface	Glossy
Shape	round
Outer diameter	87 mm
Built-in diameter	68 mm
Installation depth	55 mm
weight	0.122 kg

recessed ceiling spot

Artikel-Nr. 1928.05

Licht.
Für Generationen.

Operating technology of the luminaires	
System output	50 W
Voltage type	AC/DC
AC nominal voltage max	12 V
Frequenz max.	50 Hz
Lamp	LV halogen lamp
Lamp holder	GX5.3
Protection class	III
Degree of protection	IP20
Control	Dimming depending on driver

Mounting technology	
Mounting method	Recessed mounting
Place of installation	Ceiling-mounted
Adjustability	Pivoted
Swivel angle	25°
Further references	No cover with thermal insulation material
Circlip	Without circlip

Packing data	
Gross weight	0.158 kg
Packaging width	85 mm
Packaging height	68 mm
Length of packaging	75 mm

Compatible LED-modules						
Artikel-Nr.	Power	Beam angle	Colour temperature	Luminous flux	Input	Height LED-Modul
12925003	3 W	38°	2700 K	290 lm	350 mA	40 mm