



Special features

- High light emission angle
- Flat installation height

Housing Material	Die-cast aluminium
Housing Color	Grey
Protection Class	Protection class III/safety extra-low voltage
Operating Mode	Constant current
Rated Input	16 W
Rated Input Voltage	23-24 V/DC
Rated Current	700 mA
Power Supply Unit incl.	No
Connection Cable Secondary	Yes
Secondary Connection	Open cables
Dimmable	Yes
Control technology	Dimmable via optional power supply unit
Motion Detector	No

Cut Out Width	215 mm
Product weight	635 g
Working Temperature	-5 to 40 °C
Storage Temperature	-10 to 60 °C
IP Protection Class	IP 20
Life Time L70 / B50	50000 h
Switching Cycles	100000
Power Consumption	17 kWh/1000h
Energy Efficiency Class	G

Light Source	LED, Light source not changeable
Color Temperature	2700 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	1560 lm
Luminous Efficiency	97.5 lm/W
Rated Angle of Reflection	110 Degree
Light Distribution	Symmetric
Distribution Characteristic 120°	DLS

Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below

Length	237 mm
Width	237 mm
Height	20 mm
Installation Depth	20 mm
Cut Out Length	215 mm