
BRUMBERG

LED converter 350mA, ZigBee dimmable

Article no. 17671020

Light. For Generations.







Tender

LED converter 350mA, ZigBee dimmable. This driver fulfills the requirements for safety lighting systems in accordance with DIN EN 50172 VDE 0108-100:2005-01. This converter is equipped with safety devices which protect it against overvoltage, short-circuit as well as thermal and electric overloads. The input and output terminals are suitable for cables with a cross-section of up to 1.5 mm². Material: Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) II, Current: 350 mA, Voltage: 230V AC 50Hz, Power: 18.5W, dimmable: Yes, Control: Zigbee.

Article data	
Article no.	17671020
GTIN	4251433926641
Short description	LED converter 350mA, ZigBee dimmable
Material	Plastic
Length	146 mm
Width	44 mm
Hight	30 mm
Scope of delivery	Plug&Play version with 110 mm P&P output cable
Weight	0.198 kg

BRUMBERG

LED converter 350mA, ZigBee dimmable

Article no. 17671020

Light. For Generations.

Operating technology of driver	
AC nominal voltage min	198 V
AC nominal voltage max	264 V
Frequenz max.	50 Hz
DC nominal voltage min	198 V
DC nominal voltage max	276 V
Current	350 mA
Protection class	II
Degree of protection	IP20
Starting current	5A (50µs)
Power min	3.5 W
Power	18.5 W
Control	Zigbee
Enviroment temprature (ta)	-25 °C bis +45 °C
Measure point (tc)	max. +80 °C
Version	Plug&Play + connection box
Power factor	0.95

Packing data	
Gross weight	0.265 kg
Length of packaging	140 mm
Packaging width	110 mm
Packaging hight	120 mm
Disposal at end of life	This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately.
	By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that
	harmful substances get into the environment.