

DSUB SV MA SSDP ANG73-254 15PPL2 NUT4-40



Image is for illustration purposes only. Please refer to product description.

| | |
|--------------------|---|
| Part number | 09 65 223 6802 |
| Specification | DSUB SV MA SSDP ANG73-254 15PPL2 NUT4-40 |
| HARTING eCatalogue | https://b2b.harting.com/09652236802 |

Identification

| | |
|----------------------------|-------------------|
| Category | Connectors |
| Series | D-Sub |
| Identification | Standard |
| Element | Connector |
| Description of the contact | Stamped Angled |

Version

| | |
|--------------------|------------------------------------|
| Termination method | Wave soldering termination |
| Gender | Male |
| Size | D-Sub 2 |
| Connection type | Motherboard to daughtercard |
| Number of contacts | 15 |
| Termination length | 2.9 mm |
| Locking type | Fixing flange with thread 4-40 UNC |

Technical characteristics

| | |
|------------------------------------|---------------------|
| Distance between rows | 2.84 mm |
| Contact spacing (termination side) | 2.74 mm |
| Rated current | 6.5 A |
| Clearance distance | ≥1 mm |
| Creepage distance | ≥1 mm |
| Insulation resistance | >10 ¹⁰ Ω |



Pushing Performance
Since 1945

Technical characteristics

| | |
|---------------------------|-------------------------------|
| Contact resistance | ≤10 mΩ |
| Tightening torque | ≤0.6 Nm Female screw lock |
| Limiting temperature | -55 ... +125 °C |
| Insertion force | ≤50 N |
| Withdrawal force | ≥4.5 N ≤33 N |
| Performance level | 2 acc. to CECC 75301-802 |
| Mating cycles | ≥250 |
| Test voltage $U_{r.m.s.}$ | 1 kV |
| Isolation group | IIIa ($175 \leq CTI < 400$) |
| PCB thickness | ≥1.6 mm |
| Installation height | 7.3 mm |
| Hot plugging | No |

Material properties

| | |
|---|---|
| Material (insert) | Thermoplastic resin, glass-fibre filled (PBTP) Shell: Plated steel |
| Colour (insert) | Black |
| Material (contacts) | Copper alloy |
| Surface (contacts) | Noble metal over Ni |
| Material flammability class acc. to UL 94 | V-0 |
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | e |
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Not contained |
| California Proposition 65 substances | Yes |
| California Proposition 65 substances | Antimony trioxide Lead Nickel |
| Requirement set with Hazard Levels | R26 |



Pushing Performance
Since 1945

Specifications and approvals

| | |
|----------------|-----------------------|
| Specifications | DIN 41652 |
| UL / CSA | UL 1977 ECBT2.E102079 |

Commercial data

| | |
|--------------------------------|------------------------|
| Packaging size | 100 |
| Net weight | 10 g |
| Country of origin | Romania |
| European customs tariff number | 85366990 |
| GTIN | 5713140077713 |
| eCl@ss | 27440214 D-Sub coupler |