



Special features

- UGR less than 19
- Dimmable using controller
- Light colour adjustable using controller

Housing Material	Aluminium	Storage Temperature	-30 to 60 °C
Housing Color	White	IP Protection Class	IP 20
Protection Class	Protection class III/safety extra-low voltage	Life Time L70 / B50	30000 h
Operating Mode	Constant voltage	Switching Cycles	15000
Rated Input	67 W	Power Consumption	67 kWh/1000h
Rated Input Voltage	24 V/DC	Energy Efficiency Class	F
Power Supply Unit incl.	No		
Connection Cable Secondary	Yes		
Secondary Connection	Open cables		
Secondary Cable Length	3 m		
Dimmable	Yes		
Control technology	Dimmable via optional controller		
Motion Detector	No		
Light Source	LED, Light source not changeable		
Color Temperature	4000 K		
Colour Consistency	6 SDCM		
Colour Rendering Index (Ra)	80		
Rated Luminous Flux	3540 lm		
Luminous Efficiency	52.8 lm/W		
Rated Angle of Reflection	120 Degree		
Distribution Characteristic 120°	DLS		
Light Exit Surfaces	1		
Light characteristics	Direct		
Light direction	Below		
Length	1195 mm		
Width	295 mm		
Height	13.8 mm		
Product weight	3580 g		
Working Temperature	-20 to 40 °C		

