

**Special features**

- Very low glare value
- Service life 50,000 h L80B10
- Dimmable using touch sensor
- Ready to use

Housing Material	Aluminium	Length	610 mm
Housing Color	Silver	Width	310 mm
Material of Lens	Acryl	Height	1950 mm
Colour of Lens	White	Base length	460 mm
		Base width	300 mm
Protection Class	Protection class I/protective grounding	Base height	8 mm
Rated Input	80 W	Product weight	12755 g
Rated Input Voltage	220-240 V/AC 50 / 60 Hz	Working Temperature	-20 to 45 °C
Frequency		Storage Temperature	-40 to 80 °C
Power Supply Unit incl.	Yes	IP Protection Class	IP 20
Connection Cable Primary	Yes	Life Time L70 / B50	50000 h
Primary Connection	Power plug	Life Time L80 / B10	50000 h
Primary Cable Length	1.5 m	Switching Cycles	25000
Connection Type According to Standard	Typ X	Power Consumption	80 kWh/1000h
Dimmable	Yes	Energy Efficiency Class	F
Control technology	Touch-Sensor		
Motion Detector	No		
Light Source	LED, Light source not changeable		
Lightcolor	Neutral white		
Color Temperature	4000 K		
Colour Consistency	6 SDCM		
Colour Rendering Index (Ra)	80		
Rated Luminous Flux	7400 lm		
Luminous Efficiency	92.5 lm/W		
Rated Angle of Reflection	110 Degree		
Rated Angle of Reflection 2	90 Degree		
UGR	19		
Distribution Characteristic 120°	DLS		
Light Exit Surfaces	2		
Light characteristics	Direct		
Light direction	Top, Below		