

## M23 HBM back M25



Image is for illustration purposes only. Please refer to product description.

Part number	09 15 100 0308
Specification	M23 HBM back M25
HARTING eCatalogue	<a href="https://b2b.harting.com/09151000308">https://b2b.harting.com/09151000308</a>

### Identification

Category	Hoods/Housings
Series	Circular connectors M23
Identification	Signal
Type of hood/housing	Bulkhead mounted housing
Description of hood/housing	Rear mounting

### Version

Size	M23
Fixing	Thread M25 x 1.5
Locking type	Screw locking
Details	Not compatible to ComLock

### Technical characteristics

Limiting temperature	-40 ... +125 °C
Degree of protection acc. to IEC 60529	IP67 locked condition IP69 / IPX9K acc. to ISO 20653 locked condition

### Material properties

Material (hood/housing)	Copper-zinc alloy
Surface (hood/housing)	Nickel plated
Material (seal)	NBR
Colour (seal)	Black
RoHS	compliant



**Pushing Performance**  
Since 1945

## Material properties

ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead Nickel

## Specifications and approvals

UL / CSA	UL 1977 ECBT2.E235076
----------	-----------------------

## Commercial data

Packaging size	5
Net weight	47.4 g
Country of origin	Germany
European customs tariff number	85389099
GTIN	5713140184176
eCl@ss	27440224 Shell for circular connectors