



Ceiling lights in the LUCEA series are available with or without mount in the 10, 15, 20 and 30 watt output levels. The variants with mount can also be rotated and swivelled. They provide up to 2,900 lumens of light output depending on the design. The light emission angle can be narrowed or expanded by exchanging optionally available lenses.

Special features

- High colour rendering
- Light colour adjustable in 2 stages
- Housing made from die-cast aluminium
- Dimmable

Housing Material	Aluminium	Life Time L70 / B50	50000 h
Housing Color	White	Switching Cycles	100000
Material of Lens	PMMA	Power Consumption	6 kWh/1000h
Protection Class	Protection class I/protective grounding	Energy Efficiency Class Lightsource	This product contains a light source of energy efficiency class E.
Rated Input	6 W		
Rated Input Voltage Frequency	200-240 V/AC 50 / 60 Hz		
Power Supply Unit incl.	Yes		
Connection Type	Clamp		
Dimmable	Yes		
Control technology	Leading-edge dimmer, Trailing-edge dimmer		
Motion Detector	No		
Light Source	LED, Light source changeable TC		
Color Temperature	2700 K		
Colour Consistency	3 SDCM		
Colour Rendering Index (Ra)	90		
Rated Luminous Flux	800 lm		
Rated Angle of Reflection	36 Degree		
UGR	16		
Light Distribution	Symmetric		
Light Exit Surfaces	1		
Light characteristics	Direct		
Light direction	Below		
Height	157 mm		
Diameter	65 mm		
Working Temperature	-20 to 40 °C		
Storage Temperature	-20 to 65 °C		
IP Protection Class	IP 20		