

M23 HBM back M2,5



Part number 09 15 100 0305

Specification M23 HBM back M2,5

HARTING eCatalogue https://b2b.harting.com/09151000305

Image is for illustration purposes only. Please refer to product description.

Identification

Category	Hoods/Housings
Series	Circular connectors M23
Identification	Signal
Type of hood/housing	Bulkhead mounted housing
Description of hood/housing	Rear mounting

Version

Size	M23
Fixing	Thread 4x M2.5
Locking type	Screw locking ComLock rapid locking

Technical characteristics

Limiting temperature	-40 +125 °C
Degree of protection acc. to IEC 60529	IP67 locked condition
	IP69 / IPX9K acc. to ISO 20653 locked condition

Material properties

Material (hood/housing)	Copper-zinc alloy
Surface (hood/housing)	Nickel plated
Material (seal)	NBR
Colour (seal)	Black
RoHS	compliant
ELV status	compliant



Material properties

China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead Nickel

Specifications and approvals

UL / CSA UL 1977 ECBT2.E235076			
UL / CSA UL 1917 ECD12.E233070	III / CCA	III 1077 ECDTO E025076	
	UL / CSA	UL 1977 ECD12.E233070	

Commercial data

oonmoroidi data	
Packaging size	5
Net weight	25.9 g
Country of origin	Germany
European customs tariff number	85389099
GTIN	5713140184152
eCl@ss	27440224 Shell for circular connectors