



<b>Housing Material</b>	Aluminium	<b>Switching Cycles</b>	100000
<b>Housing Color</b>	White	<b>Energy Efficiency Class Lightsource</b>	This product contains a light source of energy efficiency class F.
<b>Material of Lens</b>	PMMA		
<b>Functions</b>	Dim to warm		
<b>Protection Class</b>	Protection class I/protective grounding		
<b>Rated Input</b>	10 W		
<b>Rated Input Voltage Frequency</b>	200-240 V/AC 50 / 60 Hz		
<b>Power Supply Unit incl.</b>	Yes		
<b>Connection Type</b>	Adapter		
<b>Dimmable</b>	Yes		
<b>Control technology</b>	Leading-edge dimmer, Trailing-edge dimmer		
<b>Motion Detector</b>	No		
<b>Light Source</b>	LED, Light source changeable TC		
<b>Lightcolor</b>	Warm white (WW)		
<b>Colour Temperature</b>	1800-2700 K		
<b>Colour Rendering Index (Ra)</b>	90		
<b>Rated Luminous Flux</b>	750 lm		
<b>Luminous Efficiency</b>	75 lm/W		
<b>Rated Angle of Reflection</b>	36 Degree		
<b>Light Distribution</b>	Symmetric		
<b>Height</b>	157 mm		
<b>Diameter</b>	65 mm		
<b>Pendulum Length max.</b>	1800 mm		
<b>Product weight</b>	550 g		
<b>Working Temperature</b>	-20 to 40 °C		
<b>Storage Temperature</b>	-20 to 65 °C		
<b>IP Protection Class</b>	IP 20		
<b>Life Time L70 / B50</b>	50000 h		