



With its extraordinary mix of materials consisting of die-cast aluminium housing and concrete base, just on looks the CHERTAN outdoor standing light certainly stands apart from other models. With its pleasantly warm white light and light emission angle of 120° including movement and twilight sensor, the outdoor light is perfectly suited for decorative use in entrance areas, on paths or in the garden.

Special features

- Base L x W x H: 160 x 30 x 40 mm
- Movement/twilight sensor

Housing Material	Die-cast aluminium	Storage Temperature	-10 to 60 °C
Housing Color	Grey	IP Protection Class	IP 54
Material of Lens	Plastic	Life Time L70 / B50	30000 h
Protection Class	Protection class I/protective grounding	Switching Cycles	15000
Rated Input	13 W	Power Consumption	13 kWh/1000h
Rated Input Voltage Frequency	100-277 V/AC 50 / 60 Hz	Energy Efficiency Class	G
Power Supply Unit incl.	Yes		
Connection Cable Primary	Yes		
Primary Connection	Connection box IP54		
Dimmable	No		
Motion Detector	No		
Light Source	LED, Light source not changeable		
Color Temperature	3000 K		
Colour Consistency	6 SDCM		
Colour Rendering Index (Ra)	90		
Rated Luminous Flux	530 lm		
Rated Angle of Reflection	120 Degree		
Light Distribution	Symmetric		
Distribution Characteristic 120°	NDLS		
Light Exit Surfaces	1		
Light characteristics	Indirect		
Light direction	Below		
Length	170 mm		
Width	72 mm		
Height	600 mm		
Base length	160 mm		
Base width	30 mm		
Base height	40 mm		
Working Temperature	-20 to 50 °C		