
lightnet

Cubic-F2

Free standing luminaire - Direct/indirect light distribution





Article code: CF2ABX-840M-L600-U-A

Illustrations may only be similar and serve as an orientation.

Cubic-F2. LED. Free standing luminaire. Luminaire head with 25mm minimalist overall height. Luminaire body made of high-quality aluminum profile. Surface finish Jet Black. Direct/indirect light distribution. Colour temperature: 4000K (Cool White). Colour Rendering Index (CRI): >80. Microprismatic screen for reduced luminance in office areas. UGR<=19. Separate stepless dimming of the direct/indirect light chambers. LxWxH (luminaire head, rectangular/Stand). L=600mm. W=300mm. H=2000/25mm.


Medium-power current. 11100lm. 68W. 19,5kg. Binning initial <= MacAdam 3. U-formed floor base matching luminaire`s outer surface colour. Plug Schuko CEE 7/7 (Type E+F). IP20. Protection class I. CE, UKCA marking. Prüfzeichen: ENEC. IK02. 220-240V. 50-60 Hz. Luminous flux reduction up to 0,3%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L85B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 and 50001:2018 certified.


lightnet

Cubic-F2

Free standing luminaire - Direct/indirect light distribution







Article code: CF2ABX-840M-L600-U-A

Customer	/ Project:		
Note:			

Productname Cubic-F2 Lamp LED

Installation Type Free standing luminaire

Surface finish Jet Black

Colour temperature 4000K Colour Rendering Index (CRI) CRI>80

Optical system Microprismatic screen

Control Separately stepless dimmable

Length L/Diameter D (mm) L=600mm
Width W (mm) W=300mm
Height H (mm) H=2000/25mm
Current/Power Medium-Power
Luminous Flux 11100lm
Power consumption 68W
Base-Type U-base

Plug Schuko CEE 7/7 (E+F)

Degree of protection IP20

Certification Prüfzeichen: ENEC

LED lifetime L85B10 (tq 25° C) = 50.000h

UGR UGR<=19
Photometric code 8 40 / 3 3 9

Indoor/Outdoor Indoor: ta [ambient] max. 25°C

Weight (kg) 19,5kg

