



- Can be dimmed using Dali1/Dali2
- Can be dimmed using 230 V push button [on/off, brightness]
- Intelli-Push function [shortcut synchronises all connected power supply units when needed]
- Current range adjustable using DIP switch
- Can be operated without actuation/dimming
- Dimming range 1-100 %
- Flicker-free
- Short circuit and overload protection
- Safe against overheating

Special features

- Can be dimmed using Dali1/Dali2
- Can be dimmed using 230 V push button [on/off, brightness]
- Intelli-Push function [shortcut synchronises all connected power supply units when needed]
- Current range adjustable using DIP switch
- Can be operated without actuation/dimming
- Dimming range 1-100 %
- Flicker-free
- Short circuit/overload protection, overheating protection

Housing Material	Plastic
Housing Color	Black
Operating Mode	Constant current
Protection Class	Protection class II/protective insulation
Power	14.0-45 W
Output Voltage	14-43 V/DC
Output Current Selectable	1050 mA, 1150 mA, 1200 mA, 1300 mA, 1400 mA, 1500 mA, 1600 mA
Dimmable	Yes
Control	DALI 2 / DT6, Intelli Push-Dim
Number of Channels	1
Power Factor	0.98
Connection Type	Clamp

Number of Circuit Breaker B10A max.	12
Number of Circuit Breaker B16A max.	20
Number of Circuit Breaker C10A max.	25
Number of Circuit Breaker C16A max.	40
Inrush Current max.	55 A / 100 µs
Capacitive Load	182 nF
Reference Point Tc	80 °C
Working Temperature	-20 to 50 °C
Storage Temperature	-20 to 70 °C
IP Protection Class	IP 20

Length	135 mm
Width	72 mm
Height	24 mm
Product weight	171 g

Multi-CC variable power/voltage ranges		
Current	Power	Voltage
1050mA	14,70W - 45,00W	14V - 43V
1150mA	16,10W - 45,00W	14V - 39V
1200mA	16,80W - 45,00W	14V - 38V
1300mA	18,20W - 45,00W	14V - 35V
1400mA	19,60W - 45,00W	14V - 32V
1500mA	21,00W - 45,00W	14V - 30V
1600mA	22,40W - 45,00W	14V - 28V

max. 2 lamps per channel - check voltage range!

