



Modern elegance for ceilings; the ceiling lights from the SCULPTORIS series can be used in a number of ways indoors thanks to different outputs, sizes and colour temperatures. The surface-mounted ceiling lights provide extensive illumination for rooms and also look great as wall lights.

The light is softly and extensively diffused through the large, circumferential diffuser with matt aluminium design and illuminates rooms pleasantly and evenly.

Special features

- Light colour adjustable in 2 stages
- Uniform illumination
- Circumferential diffuser

Housing Material	Aluminium	Life Time L70 / B50	30000 h
Housing Color	White	Switching Cycles	20000
Housing Surface	Matt	Power Consumption	42 kWh/1000h
Material of Lens	Acryl	Energy Efficiency Class Lightsource	This product contains a light source of energy efficiency class E.
Surface Structure of Lens	Satined		
Protection Class	Protection class I/protective grounding		
Rated Input	42 W		
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz		
Power Supply Unit incl.	Yes		
Connection Type	Clamp		
Dimmable	Yes		
Control technology	Leading-edge dimmer, Trailing-edge dimmer		
Motion Detector	No		
Light Source	LED, Light source changeable TC		
Color Temperature	3000/4000 K		
Colour Consistency	6 SDCM		
Colour Rendering Index (Ra)	80		
Rated Luminous Flux	3000/3100 lm		
Rated Luminous Flux 2	3100 lm		
Rated Angle of Reflection	150 Degree		
Light Exit Surfaces	1		
Light characteristics	Direct		
Light direction	Below		
Height	130 mm		
Diameter	600 mm		
Working Temperature	-10 to 45 °C		
Storage Temperature	-10 to 45 °C		
IP Protection Class	IP 20		