



Abbildung ähnlich

Product Features

SC-D/SC-D patch cord, OM3, aqua, 5m

- MM-fibre, G50/125 Åm, grade C3 or SM-Faser E9/125Åm, grade C1
- low insertion loss
- Push-Pull - connector locking
- pre-polished ceramic ferrule, 2,5mm
- with kink protection sleeves
- life > 1000 cycles
- 5 m

Features

General

Design	plug, ceramic sleeve
Classification	OM3
Halogen Free	Yes
Country of manufacture	CN
GTIN (EAN)	4043921665183

Dimensions/Weights without packaging

Cable length mm	5.000
Cable diameter mm	3
Cable construction	50/125µm, Grade C3
Net weight piece kg	0,079

Certifications

RoHS conform	Yes
--------------	-----

Logistics Information

Packaging	polybag
Packaging unit Quantity	1
Packaging unit Weight kg	0,085
Packaging unit Width mm	180
Packaging unit Height mm	210
Packaging unit Depth mm	20

References

Accessories	228030506, 228030512, 228030524, 228030606, 228030612, 228030624, 228030706, 228030712, 228030724, 228030806, 228030812, 228030824
-------------	--

Similar article

	228050005, 228050502, 228050605, 228050705, 228050805, 228050905, 228051305
--	---