



**Special features**

- Base L x W x H: 74 x 12 x 83 mm

<b>Housing Material</b>	Die-cast aluminium
<b>Housing Color</b>	Grey
<b>Material of Lens</b>	Plastic
<b>Protection Class</b>	Protection class I/protective grounding
<b>Rated Input</b>	11.5 W
<b>Rated Input Voltage Frequency</b>	220-240 V/AC 50 / 60 Hz
<b>Power Supply Unit incl.</b>	Yes
<b>Connection Type</b>	Clamp
<b>Dimmable</b>	No
<b>Motion Detector</b>	No
<b>Light Source</b>	LED, Light source not changeable
<b>Color Temperature</b>	3000 K
<b>Colour Consistency</b>	6 SDCM
<b>Colour Rendering Index (Ra)</b>	80
<b>Rated Luminous Flux</b>	530 lm
<b>Rated Angle of Reflection</b>	113 Degree
<b>Distribution Characteristic 120°</b>	NDLS
<b>Light Exit Surfaces</b>	2
<b>Light characteristics</b>	Direct, Indirect
<b>Light direction</b>	Top, Below
<b>Length</b>	80 mm
<b>Width</b>	92 mm
<b>Height</b>	105 mm
<b>Base length</b>	74 mm
<b>Base width</b>	74 mm
<b>Base height</b>	83 mm
<b>Working Temperature</b>	-5 to 40 °C
<b>Storage Temperature</b>	-10 to 60 °C
<b>IP Protection Class</b>	IP 54

<b>IK Protection Class</b>	IK04
<b>Life Time L70 / B50</b>	30000 h
<b>Switching Cycles</b>	100000
<b>Power Consumption</b>	12 kWh/1000h
<b>Energy Efficiency Class</b>	G