

## Wall mounting socket outlet - housing dimensions 87x64



| Product description       |                             |
|---------------------------|-----------------------------|
| BALS-Prd.-Nr              | 1134                        |
| EAN                       | 4024941011341               |
| Product category          | Wall mounting socket outlet |
| Current                   | 16A                         |
| Number of poles           | 3p                          |
| Poles                     | 2P+PE                       |
| Position of earth contact | 9 h                         |
| Voltage                   | 380 up to 415V              |
| Frequency                 | 50 and 60Hz                 |

| <b>Product description</b> |  |
|----------------------------|--|
| Protection degree          | IP67   |
| Colour code                | red RAL 3000   |
| Colour of appliance        | Hinged lid red RAL 3000, Bayonet ring grey RAL 7035, Housing bottom grey RAL 7035, Housing top grey RAL 7035 |
| Connection design          | with screw terminal  |
| Maximum conductor size     | 4,0 qmm  |
| Cable entry                | top entry M20  |
| Height                     | 119mm  |
| Width                      | 71mm   |
| Depth                      | 104mm  |
| Dimension of enclosure     | 87x64 mm (HxW)   |
| Material of enclosure      | Polyamide  |
| Contact                    | The contact carrier is made of polyamide, The contacts are brass   |

| <b>Additional technical properties</b> |   |
|--|---|
|  | The cable entry is one at top open and one at bottom and one rear side closed |
|  | Lower part of housing rotatable by 180°                                       |

| <b>Logistics data</b> |                  |
|-----------------------|------------------|
| Weight/pcs            | 0.206 kg / Piece |
| Packaging             | Bag              |

| Logistics data |               |
|----------------|---------------|
| Content amount | 1 ST          |
| EAN            | 4024941011341 |
| Length         | 104 mm        |
| Width          | 71 mm         |
| Height         | 119 mm        |
| Weight         | 0.207 kg      |
| Volume         | 878.696 ccm   |
| Packaging      | Carton        |
| Content amount | 10 ST         |
| EAN            | 4024941959889 |
| Length         | 258 mm        |
| Width          | 183 mm        |
| Height         | 212 mm        |
| Weight         | 2.212 kg      |
| Volume         | 8,750 ccm     |



1 MB 13

| Ampere                     | 16      | 16      | 16      | 32      | 32      | 32      |
|----------------------------|---------|---------|---------|---------|---------|---------|
| Polzahl                    | 3       | 4       | 5       | 3       | 4       | 5       |
| a                          | 64,0    | 75,0    | 75,0    | 83,0    | 83,0    | 83,0    |
| b                          | 87,0    | 100,0   | 100,0   | 126,0   | 126,0   | 126,0   |
| c                          | 115,0   | 130,0   | 130,0   | 160,0   | 160,0   | 160,0   |
| d                          | 103,0   | 110,0   | 115,0   | 129,0   | 129,0   | 135,0   |
| e                          | 51,0    | 59,0    | 59,0    | 68,0    | 68,0    | 68,0    |
| f                          | 20,0    | 11,0    | 11,0    | 11,0    | 11,0    | 11,0    |
| g                          | 20,0    | -       | -       | -       | -       | -       |
| h ø                        | 4,1     | 5,1     | 5,1     | 5,5     | 5,5     | 5,5     |
| i                          | 4,5     | 4,5     | 4,5     | 6,5     | 6,5     | 6,5     |
| k ø                        | 8,0     | 10,0    | 10,0    | 12,0    | 12,0    | 12,0    |
| l                          | -       | -       | -       | 65,0    | 65,0    | 65,0    |
| m                          | -       | -       | -       | 80,0    | 80,0    | 80,0    |
| n ø                        | -       | -       | -       | 10,0    | 10,0    | 10,0    |
| o                          | M20     | M20     | M20     | M25     | M25     | M25     |
| p                          | für M20 | für M20 | für M20 | 2 x M25 | 2 x M25 | 2 x M25 |
| Leiter mm <sup>2</sup> min | 1,5     | 1,5     | 1,5     | 2,5     | 2,5     | 2,5     |
| Leiter mm <sup>2</sup> max | 4       | 4       | 4       | 10      | 10      | 10      |