



The new COLT series is a genuine all-rounder outdoors: Powerful, freely rotatable and tiltable and equipped with the latest LED technology, the surface-mounted lamps deliver atmospheric illumination concepts in any outdoor application and cut a fine figure even when switched off thanks to their striking design.

Special features

- Replaceable reflectors
- Including clear/frosted glass pane
- Including honeycomb filter
- Feed-through wiring possible

Housing Material	Die-cast aluminium
Housing Color	Black
Material of Lens	Glass
Protection Class	Protection class I/protective grounding
Rated Input	14 W
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Connection Type	Clamp
Dimmable	Yes
Control technology	Leading-edge dimmer, Trailing-edge dimmer
Motion Detector	No

Storage Temperature	-40 to 80 °C
IP Protection Class	IP 65
Life Time L70 / B50	50000 h
Switching Cycles	15000
Power Consumption	15 kWh/1000h
Energy Efficiency Class	G

Light Source	LED, Light source not changeable
Color Temperature	3000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	1090 lm
Rated Angle of Reflection	40 Degree
Light Distribution	Symmetric
Distribution Characteristic 120°	DLS

Swivel Angle	180 Degree
Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Top

Length	88.3 mm
Height	220 mm
Diameter	110.5 mm
Base height	56 mm
Base diameter	120 mm

Working Temperature	-30 to 40 °C
----------------------------	--------------