



In the ceiling or on the ceiling - the LED PANEL 3K SMALL impresses in any variant. In addition to the optionally available frame for ceiling recessing or ceiling mounting, the compact LED Panel (optionally available as 3,000 K or 4,000 K version) can be flexibly dimmed using a separate power supply. This makes the LED PANEL 3K SMALL a capable modern ceiling light for office spaces, public administration buildings, catering establishments and many others.

Special features

- Recessed or surface mounting possible
- High colour reproduction value
- High light emission angle
- Including 50 cm connecting cable

Housing Material	Aluminium
Housing Color	White
Housing Surface	Matt
Material of Lens	Plastic
Surface Structure of Lens	Opal
Protection Class	Protection class III/safety extra-low voltage
Operating Mode	Constant current
Rated Input	24 W
Rated Input Voltage	34-35 V/DC
Rated Current	700 mA
Power Supply Unit incl.	No
Connection Cable Secondary	Yes
Secondary Connection	Open cables
Secondary Cable Length	0.5 m
Dimmable	Yes
Control technology	Dimmable via optional power supply unit
Motion Detector	No

Width	295 mm
Height	10 mm
Product weight	860 g
Working Temperature	-5 to 40 °C
Storage Temperature	-10 to 40 °C
IP Protection Class	IP 20
Life Time L70 / B50	30000 h
Switching Cycles	100000
Power Consumption	25 kWh/1000h
Energy Efficiency Class	G

Light Source	LED, Light source not changeable
Color Temperature	4000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	2500 lm
Luminous Efficiency	104.2 lm/W
Rated Angle of Reflection	115 Degree
Light Distribution	Symmetric
Distribution Characteristic 120°	DLS
Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below

Length 295 mm

