

**Special features**

- 230 V direct connection
- Including power supply

Housing Material	Aluminium	Storage Temperature	-40 to 80 °C
Housing Color	White	IP Protection Class	IP 40
Material of Lens	Plastic	IK Protection Class	IK03
Protection Class Lamp	Protection class II/protective insulation	Life Time L70 / B50	50000 h
Protection Class Power Plug	Protection class III/safety extra-low voltage	Switching Cycles	100000
Rated Input	30.5 W	Power Consumption	31 kWh/1000h
Rated Input Voltage	220-240 V/AC	Energy Efficiency Class	E
Power Supply Unit incl.	Yes		
Connection Type	Clamp		
Dimmable	No		
Motion Detector	No		
Light Source	LED, Light source changeable TC		
Color Temperature	3000 K		
Colour Consistency	6 SDCM		
Colour Rendering Index (Ra)	80		
Rated Luminous Flux	3880 lm		
Luminous Efficiency	127.2 lm/W		
Rated Angle of Reflection	120 Degree		
UGR	22		
Light Exit Surfaces	1		
Light characteristics	Direct		
Light direction	Below		
Length	595 mm		
Width	595 mm		
Height	32 mm		
Cut Out Length	570 mm		
Cut Out Width	570 mm		
Product weight	1577 g		
Working Temperature	-20 to 45 °C		