

## M12 A 4pol m/f st/an PUR shld 0,3mt



Image is for illustration purposes only. Please refer to product description.

Part number	21 34 787 7474 003
Specification	M12 A 4pol m/f st/an PUR shld 0,3mt
HARTING eCatalogue	<a href="https://harting.com/21347877474003">https://harting.com/21347877474003</a>

### Identification

Category	System cabling
Series	Circular connectors M12
Element	Cable assemblies
Specification	Pre-assembled on both sides
Connector 1	M12 A-coding Male Straight
Connector 2	M12 A-coding Female Angled
Type of cable	Copper cable (round)

### Version

Cable length	0.3 m
Number of cores	4
Core structure	4x 0.34 mm <sup>2</sup>
Shielding	Shielded
Coding	A-coding

### Technical characteristics

Limiting temperature	-30 ... +80 °C
----------------------	----------------

### Material properties

Material (cable)	PUR (polyurethane)
Colour (cable)	Black
RoHS	compliant with exemption

## Material properties

RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes
REACH SVHC substances	Lead
ECHA SCIP number	567c8b78-5fa0-43aa-a4c0-beb9d99b7769
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead Nickel

## Commercial data

Packaging size	10
Net weight	41 g
Country of origin	Germany
European customs tariff number	85444290
GTIN	5713140265028
eCl@ss	27060311 Assembled sensor actuator-line
ETIM	EC002599
UNSPSC 24.0	26121604